Sikagard®-680 S

Version 1.0 SDS Number: 000000003787 Revision Date: 2016/04/07

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikagard®-680 S

Product code : 00000003787

Type of product : liquid

Recommended use of the chemical and restrictions on use

Product use : Surfaces protection

Manufacturer or supplier's details

Company : Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000

Thailand

Telephone : +66 3810 9500

Emergency telephone num-

ber

: +66 3821 4270-85

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation : Category 3

Serious eye damage/eye irri-

tation

: Category 1

Specific target organ toxicity -

single exposure

: Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity -

repeated exposure (Inhala-


tion)

: Category 1 (Central nervous system)

Chronic aquatic toxicity : Category 2

GHS label elements

Sikagard®-680 S



Hazard pictograms











Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H316 Causes mild skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure if inhaled. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P314 Get medical advice/ attention if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Sikagard®-680 S



Version 1.0 SDS Number: 000000003787 Revision Date: 2016/04/07

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)	
Hydrocarbons, C9, aromatics	64742-95-6	>= 50 - < 70	
Hydrocarbons, C8-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	>= 10 - < 20	
2-methylpropan-1-ol	78-83-1	>= 1 -< 10	
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	>= 1 -< 10	

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: irritant effects Cough

Respiratory disorder

Excessive lachrymation

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Causes mild skin irritation.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Sikagard®-680 S

SDS Number: 00000003787 Revision Date: 2016/04/07 Version 1.0

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

: Alcohol-resistant foam Suitable extinguishing media

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: Water

High volume water jet

Specific hazards during fire-

fighting

: Do not use a solid water stream as it may scatter and spread

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

Specific extinguishing meth-

ods

: Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

7. HANDLING AND STORAGE

Advice on protection against fire and explosion

: Use explosion-proof equipment. Keep away from

heat/sparks/open flames/hot surfaces. No smoking. Take pre-

cautionary measures against electrostatic discharges.

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

Sikagard®-680 S



Version 1.0 SDS Number: 000000003787 Revision Date: 2016/04/07

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9, aromatics	64742-95-6	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
2-methylpropan-1-ol	78-83-1	TWA	50 ppm	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Sikagard®-680 S



When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point : ca. 25 °C (77 °F)

Method: closed cup

Evaporation rate : No data available

Flammability : No data available

Upper explosion limit : 6.5 %(V)

Lower explosion limit : 0.6 %(V)

Vapour pressure : 4.9996 hPa (3.750 mmHg)

Relative vapour density : No data available

Density : ca. 0.9 g/cm3 (20 ℃ (68 °F) ())

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Molecular weight : No data available

Sikagard®-680 S

Version 1.0 SDS Number: 000000003787 Revision Date: 2016/04/07

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Hydrocarbons, C8-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes mild skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if

Sikagard®-680 S

Version 1.0 SDS Number: 000000003787 Revision Date: 2016/04/07

inhaled.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9

mg/l

Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulation

UNRTDG

UN number : UN 1263
Proper shipping name : PAINT
Class : 3

Sikagard®-680 S

Version 1.0 SDS Number: 000000003787 Revision Date: 2016/04/07

Packing group : III Labels : 3

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III
Labels : 3
Packing instruction (cargo : 366

aircraft)

Packing instruction (passen: 355

ger aircraft)

IMDG-Code

UN number : UN 1263 Proper shipping name : PAINT

(naphtha (petroleum))

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

Hazardous Substance Act B.E. 2535 : Not applicable

Emergency Decree on Controlling the Use of Volatile

Substances B.E. 2533

: Not applicable

Notification of Ministry of Interior on Working Safety

Relating to Hazardous Chemicals B.E. 2534

: 2-methylpropan-1-ol

16. OTHER INFORMATION

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.