Sika® Padding Mortar



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/13

 3.0
 2020/12/04
 000000620349
 Date of first issue: 2015/09/09

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika® Padding Mortar

Product code : 000000620349

Manufacturer or supplier's details

Company : Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000 Thailand

Telephone : +66 3810 9500 Emergency telephone num- : +66 3821 4270-85

ber

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

Recommended use of the chemical and restrictions on use

Product use : Grouting mortar

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 1

Specific target organ toxicity - :

single exposure

Category 3 (Respiratory system)

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Sika® Padding Mortar



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/13

 3.0
 2020/12/04
 000000620349
 Date of first issue: 2015/09/09

Precautionary statements

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection/face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 \pm P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 50 -< 70
Cement (chromium reduced)	65997-15-1	>= 30 -< 50
Fumes, silica	69012-64-2	>= 1 -< 10

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Sika® Padding Mortar



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/13

 3.0
 2020/12/04
 000000620349
 Date of first issue: 2015/09/09

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects

Cough

Respiratory disorder Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Sika® Padding Mortar



 Version
 Revision Date:
 SDS Number:

 3.0
 2020/12/04
 000000620349

Date of last issue: 2018/06/13 Date of first issue: 2015/09/09

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions Try to prevent the material from entering drains or water

courses.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0.025 mg/m3	TH OEL

Sika® Padding Mortar



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/13

 3.0
 2020/12/04
 000000620349
 Date of first issue: 2015/09/09

		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
Cement (chromium reduced)	65997-15-1	TWA (Respirable particulate matter)	1 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Sika® Padding Mortar



Version 3.0

Revision Date: 2020/12/04

SDS Number: 000000620349

Date of last issue: 2018/06/13 Date of first issue: 2015/09/09

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : grey

Odour : odourless

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

Boiling point/boiling range

point

int

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit/Upper

flammability limit

No data available

No data available

No data available

Lower explosion limit/Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : ca. 2.3 g/cm3

Bulk density : ca. 2,000 kg/m3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic No data available

Sika® Padding Mortar



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/13

 3.0
 2020/12/04
 000000620349
 Date of first issue: 2015/09/09

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

Sika® Padding Mortar



Version 3.0

Revision Date: 2020/12/04

SDS Number: 000000620349

Date of last issue: 2018/06/13 Date of first issue: 2015/09/09

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Sika® Padding Mortar



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/13

 3.0
 2020/12/04
 000000620349
 Date of first issue: 2015/09/09

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Hazardous Substance Act : Conditions of restriction for the fol-

lowing entries should be considered:

Not applicable

Emergency Decree on Controlling the Use of Volatile

Substances

Not applicable

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
TH OEL : Thailand. Occupational Exposure Limits

ACGIH/TWA 8-hour, time-weighted average

TH OEL / TWA : Time weighted average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service

DNEL : Derived no effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

Sika® Padding Mortar



Version	Revision Date:	SDS Number:	Date of last issue: 2018/06/13
3.0	2020/12/04	00000620349	Date of first issue: 2015/09/09

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament and

of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. TH/EN