

SAFETY DATA SHEET

Sika® Primer MB Part B



Version
1.0

Revision Date:
2022/12/22

SDS Number:
100000039527

Date of last issue: -
Date of first issue: 2022/12/22

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika® Primer MB Part B

Manufacturer or supplier's details

Company : Sika (Thailand) Limited
700/37 Moo.5 Amata Nakorn Estate
Bangna-Trad Km.57
Tambol Klong Tamhru
Muang District
Chonburi 20000
Thailand

Telephone : +66 3810 9500

Emergency telephone number : +66 3821 4270-85

E-mail address : Sikathai@th.sika.com

Telefax : +66 3821 4286

2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 5

Skin corrosion/irritation : Category 1

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

SAFETY DATA SHEET

Sika® Primer MB Part B



Version 1.0 Revision Date: 2022/12/22 SDS Number: 100000039527 Date of last issue: -
Date of first issue: 2022/12/22

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H333 May be harmful if inhaled.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

SAFETY DATA SHEET

Sika® Primer MB Part B



Version
1.0

Revision Date:
2022/12/22

SDS Number:
100000039527

Date of last issue: -
Date of first issue: 2022/12/22

posal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
benzyl alcohol	100-51-6	>= 20 -< 30
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 20 -< 30
Phenol, styrenated	61788-44-1	>= 10 -< 20
m-phenylenebis(methylamine)	1477-55-0	>= 10 -< 20
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 5 -< 10
3,6,9-triazaundecamethylenediamine	112-57-2	>= 5 -< 10
Polyoxypropylene diamine	9046-10-0	>= 5 -< 10
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	25513-64-8	>= 3 -< 5

4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.

SAFETY DATA SHEET

Sika® Primer MB Part B



Version 1.0	Revision Date: 2022/12/22	SDS Number: 100000039527	Date of last issue: - Date of first issue: 2022/12/22
----------------	------------------------------	-----------------------------	--

Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.
corrosive effects
sensitising effects
Gastrointestinal discomfort
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye damage.
May be harmful if inhaled.
Causes severe burns.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

Sika® Primer MB Part B



Version: 1.0 Revision Date: 2022/12/22 SDS Number: 100000039527 Date of last issue: -
Date of first issue: 2022/12/22

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
m-phenylenebis(methylamine)	1477-55-0	C	0.018 ppm	ACGIH

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an

SAFETY DATA SHEET

Sika® Primer MB Part B



Version 1.0	Revision Date: 2022/12/22	SDS Number: 100000039527	Date of last issue: - Date of first issue: 2022/12/22
----------------	------------------------------	-----------------------------	--

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : yellow

Odour : amine-like

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 100 °C (212 °F)
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0.07 hPa

Relative vapour density : No data available

SAFETY DATA SHEET

Sika® Primer MB Part B



Version 1.0	Revision Date: 2022/12/22	SDS Number: 100000039527	Date of last issue: - Date of first issue: 2022/12/22
----------------	------------------------------	-----------------------------	--

Density : 1 - 1.1 g/cm³ (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 10 - 100 mPa.s (20 °C (68 °F))

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.
May be harmful if inhaled.

Components:

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

SAFETY DATA SHEET

Sika® Primer MB Part B



Version
1.0

Revision Date:
2022/12/22

SDS Number:
100000039527

Date of last issue: -
Date of first issue: 2022/12/22

Exposure time: 4 h
Test atmosphere: dust/mist

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

3,6,9-triazaundecamethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 1,716.2 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 1,260 mg/kg

Polyoxypropylene diamine:

Acute oral toxicity : LD50 Oral (Rat): 2,880 mg/kg

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Acute oral toxicity : LD50 Oral (Rat): 910 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Corrosive
Method : OECD Test Guideline 404

SAFETY DATA SHEET

Sika® Primer MB Part B



Version 1.0	Revision Date: 2022/12/22	SDS Number: 100000039527	Date of last issue: - Date of first issue: 2022/12/22
----------------	------------------------------	-----------------------------	--

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

SAFETY DATA SHEET

Sika® Primer MB Part B



Version 1.0	Revision Date: 2022/12/22	SDS Number: 100000039527	Date of last issue: - Date of first issue: 2022/12/22
----------------	------------------------------	-----------------------------	--

plants mg/l
Exposure time: 72 h
NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l
Exposure time: 72 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
aquatic invertebrates Exposure time: 48 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 -
plants 100 mg/l
Exposure time: 72 h

Polyoxypropylene diamine:

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l
plants Exposure time: 72 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 80 mg/l
aquatic invertebrates (Chronic toxicity) Exposure time: 48 h

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine:

Toxicity to algae/aquatic : EC50 (Scenedesmus capricornutum (fresh water algae)): 29.5
plants mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : LC50 (Leuciscus idus (Golden orfe)): 174 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

Sika® Primer MB Part B



Version 1.0	Revision Date: 2022/12/22	SDS Number: 100000039527	Date of last issue: - Date of first issue: 2022/12/22
----------------	------------------------------	-----------------------------	--

13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
-

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number or ID number : UN 2735
Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine)
Class : 8
Packing group : II
Labels : 8

IATA-DGR

- UN/ID No. : UN 2735
Proper shipping name : Amines, liquid, corrosive, n.o.s.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine)
Class : 8
Packing group : II
Labels : Corrosive
Packing instruction (cargo aircraft) : 855
Packing instruction (passenger aircraft) : 851

IMDG-Code

- UN number or ID number : UN 2735
Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine)
Class : 8
Packing group : II
Labels : 8
-

SAFETY DATA SHEET

Sika® Primer MB Part B



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	2022/12/22	100000039527	Date of first issue: 2022/12/22

EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Hazardous Substance Act : Conditions of restriction for the following entries should be considered:
Not applicable

Emergency Decree on Controlling the Use of Volatile Substances : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 28% w/w

16. OTHER INFORMATION

Revision Date : 2022/12/22
Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA ACGIH Threshold Limit Values (TLV)
ACGIH / C : Ceiling limit
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dosis (the amount of a material, given all at

SAFETY DATA SHEET

Sika® Primer MB Part B



Version 1.0	Revision Date: 2022/12/22	SDS Number: 100000039527	Date of last issue: - Date of first issue: 2022/12/22
----------------	------------------------------	-----------------------------	--

once, which causes the death of 50% (one half) of a group of test animals)

LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic

PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

TH/EN