# Sika<sup>®</sup> Separol TH

Version 3.0



#### **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name	:	Sika <sup>®</sup> Separol TH
Product code	:	000000608499
Type of product	:	liquid

#### Manufacturer or supplier's details

Company	: Sika (Thailand) Limited
	700/37 Moo. 5 Amata Nakorn Estate
	Bangna-Trad Km.57
	Tambol Klong Tamhru
	Muang District
	Chonburi 20000
	Thailand
Telephone	: +66 3810 9500
Emergency telephone num- ber	: +66 3821 4270-85
Telefax	: +66 3821 4286
E-mail address	Sikathai@th.sika.com

### 2. HAZARDS IDENTIFICATION

GHS Classification	
Flammable liquids	Category 4
Carcinogenicity	Category 2
Aspiration hazard	Category 1
Long-term (chronic) aquatic : hazard	Category 2
GHS label elements	
Hazard pictograms	
Signal word	Danger
Hazard statements :	H227 Combustible liquid. H304 May be fatal if swallowed and enters airways. H351 Suspected of causing cancer. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements :	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

## Sika<sup>®</sup> Separol TH



Version 3.0	SDS Number: 000000608499	Revision Date: 2020/0
	P273 Avoid release to the environme	ent.
	P280Wear protective gloves/eye pro	otection/face protection.
	P281 Use personal protective equipn	nent as required.
	Response:	
	P301 + P310 IF SWALLOWED: Imme	diately call a POISON
	CENTER or doctor/physician.	
	P308 + P313 IF exposed or concerne	d⊨Get medical advice/at-
	tention	
	P331 Do NOT induce vomiting.	
	P370 + P378 In case of fire: Use dry s	and, dry chemical or alco-
	hol-resistant foam for extinction.	-
	P391 Collect spillage.	
	Storage:	
	P403 + P235 Store in a well-ventilated	d place. Keep cool.
	P405 Store locked up.	
	Disposal	
	P501 Dispose of contents/ container t	to an approved waste dis-
	posal plant	

## Other hazards which do not result in classification

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration (%)
Fuels, diesel; Gasoil – unspecified	68334-30-5	>=90 -<=100
Distillates (petroleum), hydrotreated light naph-	64742-53-6	>= 1 - < 10
thenic; Baseoil – unspecified		
n-butyl acetate	123-86-4	>= 2.5 - < 10

### 4. FIRST AID MEASURES

General advice	<ul> <li>Move out of dangerous area.</li> <li>Consult a physician.</li> <li>Show this safety data sheet to the doctor in attendance.</li> </ul>
If inhaled	<ul> <li>Move to fresh air.</li> <li>Consult a physician after significant exposure.</li> </ul>
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	If eye irritation persists, consult a specialist. Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting.

# Sika<sup>®</sup> Separol TH

Version 3.0	SDS Number: 000000608499	Revision Date: 2020/06/11
Most important symptoms and effects, both acute and delayed	Do not give milk or alcoholic beverag Never give anything by mouth to an or Take victim immediately to hospital. Risk of serious damage to the lungs Aspiration may cause pulmonary oed See Section 11 for more detailed info and symptoms. May be fatal if swallowed and enters Suspected of causing cancer.	unconscious person. (by aspiration). dema and pneumonitis. ormation on health effects
Notes to physician	: Treat symptomatically.	

®

#### **5. FIREFIGHTING MEASURES**

Suitable extinguishing media Unsuitable extinguishing media	Carbon dioxide (CO2) Water	
Specific hazards during fire- fighting	Do not allow run-off from fire fighting to enter drains courses.	or water
Hazardous combustion prod- ucts	No hazardous combustion products are known	
Specific extinguishing meth- ods	Collect contaminated fire extinguishing water separ must not be discharged into drains. Fire residues and contaminated fire extinguishing w be disposed of in accordance with local regulations	/ater must
Special protective equipment for firefighters	In the event of fire, wear self-contained breathing ap	

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

#### 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	Normal measures for preventive fire protection.
Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).

# Sika<sup>®</sup> Separol TH

Version 3.0	SDS Number: 000000608499	Revision Date: 2020/06/11
	Do not get in eyes, on skin, or on clot	hing.
	For personal protection see section 8	
	Smoking, eating and drinking should plication area	be prohibited in the ap-
	Follow standard hygiene measures w products	hen handling chemical
Conditions for safe storage	<ul> <li>Store in original container.</li> </ul>	
	Keep in a well-ventilated place.	
	Containers which are opened must be kept upright to prevent leakage.	e carefully resealed and
	Observe label precautions.	
	Store in accordance with local regulat	tions.

®

1

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Fuels, diesel; Gasoil – unspec- ified	68334-30-5	TWA (Inhala- ble fraction and vapor)	100 mg/m3 (total hydrocar- bons)	ACGIH
Distillates (petroleum), hy- drotreated light naphthenic; Baseoil – unspecified	64742-53-6	TWA (Inhala- ble particu- late matter)	5 mg/m3	ACGIH
n-butyl acetate	123-86-4	TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH

### Personal protective equipment

Respiratory protection	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection	Chemical-resistant, impervious gloves complying with an ap- proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke.

# Sika<sup>®</sup> Separol TH

Version 3.0



Wash hands before breaks and at the end of workday.

0)

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colour Odour Odour Threshold	::	liquid yellow aromatic No data available
pH Melting point/range⊭Freezing point	:	Not applicable No data available
Boiling point/boiling range	:	No data available
Flash point	:	ca. 68 °C (154 °F) Method: closed cup
Evaporation rate	:	No data available
Flammability	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	1 hPa (0.75 mmHg)
Relative vapour density	:	No data available
Density	:	0.83 g/cm3 (20 °C (68 °F)
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 3.28 mm2/s (40 °C)
Explosive properties	:	No data available
Molecular weight	:	No data available

#### **10. STABILITY AND REACTIVITY**

## Sika<sup>®</sup> Separol TH

Version 3.0	SDS Number: 00000608499	Revision Date: 2020/06/11
Reactivity Chemical stability Possibility of hazardous reac- tions	<ul> <li>No dangerous reaction known under con</li> <li>The product is chemically stable.</li> <li>Stable under recommended storage conditioned storage co</li></ul>	
Conditions to avoid Incompatible materials No decomposition if stored and	<ul> <li>No data available</li> <li>No data available</li> <li>applied as directed.</li> </ul>	

#### **11. TOXICOLOGICAL INFORMATION**

#### Acute toxicity

Componento

Not classified based on available information.

<u>Components:</u>	
n-butyl acetate: Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg
Acute inhalation toxicity	ELC50 (Rat): 23.4 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	ED50 Dermal (Rabbit): > 5,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

May be fatal if swallowed and enters airways.

## Sika<sup>®</sup> Separol TH

Version 3.0



ECOLOGICAL INFORMATION	
Ecotoxicity	
<u>Components:</u>	
n-butyl acetate:	
Toxicity to algae	EC50 (Desmodesmus subspicatus (green algae)): 647.7 mg/l Exposure time: 72 h
<b>Persistence and degradability</b> No data available	
<b>Bioaccumulative potential</b> No data available	
<b>Mobility in soil</b> No data available	
Other adverse effects	
Product:	
Additional ecological infor-	Toxic to aquatic life with long lasting effects.
DISPOSAL CONSIDERATIONS	
Disposal methods	
Waste from residues	The product should not be allowed to enter drains, water courses or the soil.
	Do not contaminate ponds, waterways or ditches with chemi- cal or used container.
	Send to a licensed waste management company.
Contaminated packaging	Empty remaining contents.
	Dispose of as unused product.
	Do not re-use empty containers.

#### 14. TRANSPORT INFORMATION

#### **International Regulations**

**UNRTDG** Not regulated as a dangerous good

IATA-DGR Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

Do not burn, or use a cutting torch on, the empty drum.

# Sika<sup>®</sup> Separol TH

Version 3.0



#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **15. REGULATORY INFORMATION**

Not applicable	
Conditions of restriction for the fol- lowing entries should be considered Not applicable	
Not applicable	
Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 94 % VOC content excluding water	
1	

#### **16. OTHER INFORMATION**

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.