SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/19

 4.0
 2020/12/18
 000000610427
 Date of first issue: 2015/06/24

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaGrout®-212 GP

Product code : 000000610427

Manufacturer or supplier's details

Company : Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000 Thailand

: +66 3821 4270-85

Telephone : +66 3810 9500

Emergency telephone num-

ber

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

Recommended use of the chemical and restrictions on use

Product use : Grouting mortar

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation : Category 1

Specific target organ toxicity -

single exposure

Category 3 (Respiratory system)

GHS label elements

Hazard pictograms



Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

SikaGrout®-212 GP



Version Revision Date: 4.0 2020/12/18

SDS Number: 000000610427

Date of last issue: 2018/06/19 Date of first issue: 2015/06/24

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements

Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/eye protection/face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 50 -< 70
Cement (chromium reduced)	65997-15-1	>= 30 -< 50
sulfoaluminate clinker	Not Assigned	>= 1 -< 3

SikaGrout®-212 GP



Version Revision Date: 4.0 2020/12/18

SDS Number: 000000610427

Date of last issue: 2018/06/19 Date of first issue: 2015/06/24

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects

sensitising effects

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause respiratory irritation.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

SikaGrout®-212 GP



Version Revision Date: SDS Number: Date of last issue 2018/06/19 4.0 Date of first issue: 2015/06/24 000000610427 2020/12/18

cumstances and the surrounding environment.

Hazardous combustion prod-

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed

Advice on safe handling Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage Store in original container.

> Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/19

 4.0
 2020/12/18
 000000610427
 Date of first issue: 2015/06/24

Further information on stor-

Keep in a dry place.

age stability

No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0.025 mg/m3	TH OEL
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Sillica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
Cement (chromium reduced)	65997-15-1	TWA (Respirable particulate matter)	1 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/19

 4.0
 2020/12/18
 000000610427
 Date of first issue: 2015/06/24

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : grey

Odour : odourless

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit/Upper

flammability limit

No data available

Lower explosion limit/Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : ca. 2.2 g/cm3 (20 °C (68 °F))

Bulk density : ca. 1,470 kg/m3

Solubility(ies)

6/10

SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/19

 4.0
 2020/12/18
 000000610427
 Date of first issue: 2015/06/24

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/19

 4.0
 2020/12/18
 000000610427
 Date of first issue: 2015/06/24

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

There is no data available for this product.

mation

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/06/19

 4.0
 2020/12/18
 000000610427
 Date of first issue: 2015/06/24

Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Hazardous Substance Act : Conditions of restriction for the fol-

lowing entries should be considered:

Not applicable

Emergency Decree on Controlling the Use of Volatile

Substances

Not applicable

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
TH OEL : Thailand. Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average

TH OEL/TWA : Time weighted average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

SikaGrout®-212 GP



Version 4.0	Revision Date: 2020/12/18		SDS Number: 000000610427	Date of last issue: 2018/06/19 Date of first issue: 2015/06/24	
EC50		:	Half maximal effective cond	entration	
GHS		:	Globally Harmonized System		
IATA		:	International Air Transport Association		
IMDG		:	International Maritime Code for Dangerous Goods		
LD50		:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)		
LC50		:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)		
MARP	OL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978		
OEL		:	Occupational Exposure Limit		
PBT		:	Persistent, bioaccumulative and toxic		
PNEC		:	Predicted no effect concentration		
REACI	-1	:	of the Council of 18 Decem	06 of the European Parliament and ber 2006 concerning the Registra- on and Restriction of Chemicals ropean Chemicals Agency	
SVHC		:	Substances of Very High Concern		
vPvB		:	Very persistent and very bioaccumulative		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. TH / EN