

# SAFETY DATA SHEET

## SikaGrout®-212 HP TH



Version 4.0

SDS Number: 000000610428

Revision Date: 2019/04/04

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaGrout®-212 HP TH  
Product code : 000000610428  
Type of product : powder

#### Recommended use of the chemical and restrictions on use

Product use : Grouting mortar

#### Manufacturer or supplier's details


Company : Sika (Thailand) Limited  
700/37 Moo. 5 Amata Nakorn Estate  
Bangna-Trad Km.57  
Tambol Klong Tamhru  
Muang District  
Chonburi 20000  
Thailand  
Telephone : +66 3810 9500  
Emergency telephone number : +66 3821 4270-85  
Telefax : +66 3821 4286  
E-mail address : Sikathai@th.sika.com

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

#### GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.

# SAFETY DATA SHEET

## SikaGrout®-212 HP TH



Version 4.0

SDS Number: 000000610428

Revision Date: 2019/04/04

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration (%)
Quartz (SiO <sub>2</sub> )	14808-60-7	>= 50 - < 70
Cement (chromium reduced)	65997-15-1	>= 30 - < 50
Fumes, silica	69012-64-2	>= 1 - < 10
calcium oxide	1305-78-8	>= 1 - < 3

### 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.

# SAFETY DATA SHEET

## SikaGrout®-212 HP TH



Version 4.0

SDS Number: 000000610428

Revision Date: 2019/04/04

- Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
Cough  
Respiratory disorder  
Excessive lachrymation  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.
- Notes to physician : Treat symptomatically.

---

### 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Avoid breathing dust.  
Deny access to unprotected persons.
- Environmental precautions : Try to prevent the material from entering drains or water courses.
- Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.  
Keep in suitable, closed containers for disposal.

---

### 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Do not breathe vapours/dust.

# SAFETY DATA SHEET

## SikaGrout®-212 HP TH



Version 4.0

SDS Number: 000000610428

Revision Date: 2019/04/04

Avoid exceeding the given occupational exposure limits (see section 8).

Do not get in eyes, on skin, or on clothing.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area.

Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable dust)	0.025 mg/m <sup>3</sup>	TH OEL
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
Cement (chromium reduced)	65997-15-1	TWA (Respirable fraction)	1 mg/m <sup>3</sup>	ACGIH
calcium oxide	1305-78-8	TWA	5 mg/m <sup>3</sup>	TH OEL
		TWA	2 mg/m <sup>3</sup>	ACGIH

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

# SAFETY DATA SHEET

## SikaGrout®-212 HP TH



Version 4.0

SDS Number: 000000610428

Revision Date: 2019/04/04

- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : powder
- Colour : grey
- Odour : odourless
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : Not applicable
- Evaporation rate : No data available
- Flammability : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Density : ca. 2.2 g/cm<sup>3</sup> (25 °C (77 °F) ())
- Bulk density : ca. 1,500 kg/m<sup>3</sup>
- Solubility(ies)
- Water solubility : No data available
- Solubility in other solvents : No data available

# SAFETY DATA SHEET

## SikaGrout®-212 HP TH



Version 4.0

SDS Number: 000000610428

Revision Date: 2019/04/04

---

Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: Not applicable
Explosive properties	: No data available
Molecular weight	: No data available

---

### 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
No decomposition if stored and applied as directed.	

---

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

No data available

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

May cause respiratory irritation.

# SAFETY DATA SHEET

## SikaGrout®-212 HP TH



Version 4.0

SDS Number: 000000610428

Revision Date: 2019/04/04

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

---

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

No data available

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

### **Product:**

Additional ecological information : There is no data available for this product.

---

## 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

## 14. TRANSPORT INFORMATION

### **International Regulations**

#### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

### **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

# SAFETY DATA SHEET

## SikaGrout®-212 HP TH



Version 4.0

SDS Number: 000000610428

Revision Date: 2019/04/04

---

### 15. REGULATORY INFORMATION

#### **Safety, health and environmental regulations/legislation specific for the substance or mixture**

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Hazardous Substance Act B.E. 2535 : Not applicable

Emergency Decree on Controlling the Use of Volatile Substances B.E. 2533 : Not applicable

---

### 16. OTHER INFORMATION

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.