



BUILDING TRUST



PRODUCT DATA SHEET

LANKO 612 ACRYLIC

ACRYLIC SEALANT

DESCRIPTION

LANKO 612 ACRYLIC is single component acrylic sealant.

USES

- Interior
- Sealing crack before painting
- Recommended for porous substrates
- Substrates: wood, metal, door frame, concrete, natural stone and tile

CHARACTERISTICS / ADVANTAGES

- For joint size: 4 to 12 mm
- No primer required
- 2 Colors available: Grey , White

PRODUCT INFORMATION

Packaging	280 ml cartridge
Shelf life	24 months from the date of production, if stored properly in undamaged and unopened, original sealed packaging.
Storage conditions	Store in dry condition and protected from direct sunshine.
Colour	Grey, White
Density	1.61 g/ml

APPLICATION INFORMATION

Consumption	100 ml per 1 metre at joint size 10 mm x 10 mm (width x depth)
Ambient air temperature	+5°C to +35°C
Tack free time	30 minutes

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

Keep out of reach of children.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

- Surface must be clean, dry, free of dust, oil grease and any contaminations that could harm bonding.
- Backing rod can be used to reduce joint depth.

APPLICATION METHOD / TOOLS

Primer Preparation

- Use primer if the substrate is very porous.

Application

- Use sealant gun and squeeze into the joint.
- Compact the sealant into the joint by using putty knife. Smooth the joint with figure and soapy water.
- Remove the adhesive tape before the sealant cures.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Thailand) Limited
700/37 Moo 5 Amata City Chonburi
Industrial Estate, T. Klong Tamhru
A. Muang, Chonburi 20000, Thailand
Tel : +66 3810 9500
E-mail : sikathai@th.sika.com
Website: tha.sika.com



PRODUCT DATA SHEET
LANKO 612 ACRYLIC
May 2022, Version 02.01
02051404000000114

LANKO612ACRYLIC-en-THLANKO-(05-2022)-2-1.pdf