
### Sika® Primer-207



#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika® Primer-207

Product code : 10000005704

Type of product : liquid

#### Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent

#### Manufacturer or supplier's details

Company : Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000 Thailand

: +66 3810 9500

Telephone Emergency telephone num-: +66 3821 4270-85

ber

: +66 3821 4286 Telefax E-mail address : Sikathai@th.sika.com

#### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Flammable liquids : Category 2

Serious eye damage/eye irri-

tation

: Category 2A

Skin sensitisation : Category 1

Specific target organ toxicity -

single exposure

: Category 3 (Central nervous system)

#### **GHS** label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

: Prevention: Precautionary statements

### Sika® Primer-207



Version 2.0 SDS Number: 100000005704 Revision Date: 2018/07/04

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### **Hazardous components**

Chemical name	CAS-No.	Concentration (%)
ethyl acetate	141-78-6	>= 30 - < 50
butanone	78-93-3	>= 30 - < 50
aromatic polyisocyanate	53317-61-6	>= 1 - < 10
tris(p-isocyanatophenyl) thiophosphate	4151-51-3	>= 1 - < 10
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 0.1 - < 1

### Sika® Primer-207



SDS Number: 10000005704 Revision Date: 2018/07/04 Version 2.0

#### 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

: Immediately flush eye(s) with plenty of water. In case of eye contact

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: irritant effects

sensitising effects Allergic reactions

**Excessive lachrymation** 

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause drowsiness or dizziness.

Notes to physician : Treat symptomatically.

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: Water

High volume water jet

Specific hazards during fire-

fighting

Hazardous combustion prod-

ucts

: Do not use a solid water stream as it may scatter and spread

: No hazardous combustion products are known

Specific extinguishing meth-

ods

: Use water spray to cool unopened containers.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

### Sika® Primer-207

SDS Number: 10000005704 Revision Date: 2018/07/04 Version 2.0

for firefighters

#### 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emergency procedures

Personal precautions, protec- : Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.

Environmental precautions

: Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### 7. HANDLING AND STORAGE

Advice on protection against fire and explosion

: Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Advice on safe handling

Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage

: Store in original container.

Store in cool place.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

### Sika® Primer-207



Version 2.0 SDS Number: 100000005704 Revision Date: 2018/07/04

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyl acetate	141-78-6	TWA	400 ppm	TH OEL
		TWA	400 ppm	ACGIH
butanone	78-93-3	TWA	200 ppm	TH OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.005 ppm	ACGIH

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

## Sika® Primer-207

Version 2.0 SDS Number: 100000005704 Revision Date: 2018/07/04

Colour : black

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point

: No data available

Boiling point/boiling range : No data available

Flash point :  $-4 \, ^{\circ}\text{C} \, (25 \, ^{\circ}\text{F})$ 

Method: closed cup

Evaporation rate : No data available

Flammability : No data available

Upper explosion limit : 11.5 %(V)

Lower explosion limit : 1.8 %(V)

Vapour pressure : 99.9915 hPa (75.000 mmHg)

Relative vapour density : No data available

Density : ca. 0.97 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 15 mPa.s (20 ℃)

Viscosity, kinematic : < 20.5 mm2/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

#### 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

### Sika® Primer-207

Version 2.0 SDS Number: 100000005704 Revision Date: 2018/07/04

Possibility of hazardous reac-

tions

: Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

Hazardous decomposition

products

: methanol

#### 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Not classified based on available information.

#### **Components:**

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

butanone:

Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

aromatic polyisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

tris(p-isocyanatophenyl) thiophosphate:

Acute oral toxicity : LD50 Oral (Rat): > 675 mg/kg

Remarks: see user defined free text

Acute inhalation toxicity : LC50 (Rat): 5.721 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l

Test atmosphere: dust/mist Method: Expert judgement

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

### Sika® Primer-207



Version 2.0 SDS Number: 100000005704 Revision Date: 2018/07/04

### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause drowsiness or dizziness.

#### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

No data available

### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

#### **Product:**

Additional ecological infor-

mation

: There is no data available for this product.

### 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.


Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### Sika® Primer-207



#### 14. TRANSPORT INFORMATION

### International Regulations

**UNRTDG** 

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3

**IATA-DGR** 

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3
Packing group : II
Labels : 3
Packing instruction (cargo : 364

aircraft)

Packing instruction (passen: 353

ger aircraft)

**IMDG-Code** 

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

Hazardous Substance Act B.E. 2535 : Not applicable

Emergency Decree on Controlling the Use of Volatile

Substances B.E. 2533

ethyl acetate

butanone

VOC-EU (solvent) : 661.03 g/l

### **16. OTHER INFORMATION**

Date format : yyyy/mm/dd

# Sika® Primer-207



Version 2.0 SDS Number: 100000005704 Revision Date: 2018/07/04

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.