## Sikadur®-42TH Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/07/04

 3.0
 2020/12/17
 000000611677
 Date of first issue: 2015/09/09

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikadur®-42TH Part A

Product code : 000000611677

Manufacturer or supplier's details

Company : Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000 Thailand

Telephone : +66 3810 9500 Emergency telephone num- : +66 3821 4270-85

ber

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

Recommended use of the chemical and restrictions on use
Product use : Epoxy-Cementitious system

### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic

: Category 2

hazard

Long-term (chronic) aquatic

Category 2

hazard

**GHS** label elements

Hazard pictograms





Signal word : Warning

## Sikadur®-42TH Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/07/04

 3.0
 2020/12/17
 000000611677
 Date of first issue: 2015/09/09

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

#### Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection/ face protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

P337 + P313 If eye irritation persists: Get medical advice/atten-

tion

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

## Disposal:

P501 Dispose of contents/container to an approved waste disposal plant.

#### Other hazards which do not result in classification

None known.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin);	25068-38-6	>= 70 -< 90
epoxy resin (number average molecular weight		
≤ 700)		
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 1 -< 10
(1-methylethyl)-1,1'-biphenyl	25640-78-2	>= 2.5 -< 10

## Sikadur®-42TH Part A



Version Revision Date: SDS Number: Date of last issue: 2018/07/04 3.0 2020/12/17 000000611677 Date of first issue: 2015/09/09

**4. FIRST AID MEASURES** 

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects

sensitising effects Allergic reactions

Excessive lachrymation

**Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Notes to physician : Treat symptomatically.

### **5. FIREFIGHTING MEASURES**

Suitable extinguishing media . Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

## Sikadur®-42TH Part A



Version Revision Date: SDS Number: Date of last issue: 2018/07/04 3.0 000000611677 Date of first issue: 2015/09/09 2020/12/17

Specific extinguishing meth-

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

#### **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

## Sikadur®-42TH Part A



Version 3.0

Revision Date: 2020/12/17

SDS Number: 000000611677

Date of last issue: 2018/07/04 Date of first issue: 2015/09/09

#### **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous

Colour : colourless

Odour : very faint

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point

No data available

## Sikadur®-42TH Part A



Version Revision Date: SDS Number: Date of last issue: 2018/07/04 3.0 2020/12/17 000000611677 Date of first issue: 2015/09/09

Boiling point/boiling range No data available

Flash point > 101 °C (> 214 °F)

(Method: closed cup)

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit/Upper

flammability limit

No data available

Lower explosion limit/Lower

flammability limit

No data available

0.01 hPa Vapour pressure

Relative vapour density No data available

Density ca. 1.15 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility No data available

No data available Solubility in other solvents

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature

No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic 1,500 - 2,300 mPa.s (20 °C (68 °F))

Viscosity, kinematic ca. > 20.5 mm2/s (40 °C (104 °F))

Explosive properties No data available

Oxidizing properties No data available

#### 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

## Sikadur®-42TH Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2018/07/04

 3.0
 2020/12/17
 000000611677
 Date of first issue: 2015/09/09

Conditions to avoid : No data available

Incompatible materials : No data available

## 11. TOXICOLOGICAL INFORMATION

#### **Acute toxicity**

Not classified based on available information.

#### Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

### Skin sensitisation

May cause an allergic skin reaction.

### **Respiratory sensitisation**

Not classified based on available information.

## Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

## STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

## Sikadur®-42TH Part A



Version 3.0

Revision Date: 2020/12/17

SDS Number: 000000611677

Date of last issue: 2018/07/04 Date of first issue: 2015/09/09

#### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

### Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h

(1-methylethyl)-1,1'-biphenyl:

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 0.167 mg/l

Exposure time: 48 h

### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological infor-

mation

Toxic to aquatic life with long lasting effects.

#### 13. DISPOSAL CONSIDERATIONS

## **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

## Sikadur®-42TH Part A



Version Revision Date: SDS Number: Date of last issue: 2018/07/04 2020/12/17 000000611677 Date of first issue: 2015/09/09

#### 14. TRANSPORT INFORMATION

### **International Regulations**

**UNRTDG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

(epoxy resin, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.)

Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.)

Class : 9
Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

964

964

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F

Marine pollutant : no

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## Sikadur®-42TH Part A



Version Revision Date: 3.0 2020/12/17

SDS Number: 000000611677

Date of last issue: 2018/07/04
Date of first issue: 2015/09/09

#### 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Hazardous Substance Act

Conditions of restriction for the following entries should be considered:

Not applicable

Emergency Decree on Controlling the Use of Volatile

Substances

Not applicable

Volatile organic compounds

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content; 0.39 %

VOC content excluding water

:

## **16. OTHER INFORMATION**

Date format : yyyy/mm/dd

Full text of other abbreviations

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS Chemical Abstracts Service

DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament and

# Sikadur®-42TH Part A



Version Revision Date: SDS Number: Date of last issue: 2018/07/04 3.0 2020/12/17 000000611677 Date of first issue: 2015/09/09

of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. TH / EN