## SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:

 6.0
 2024/07/25
 000000610427

Date of last issue: 2023/01/05
Date of first issue: 2015/06/24

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaGrout®-212 GP

Manufacturer or supplier's details

Company : Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000

Thailand

Telephone : +66 3810 9500

Emergency telephone number : +66 3821 4270-85

E-mail address : Sikathai@th.sika.com

Telefax : +66 3821 4286

Recommended use of the chemical and restrictions on use

Product use : Grouting mortar

#### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation : Category 1

Specific target organ toxicity - :

single exposure

Category 3 (Respiratory system)

**GHS** label elements

Hazard pictograms





Signal word : Danger

## SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2023/01/05

 6.0
 2024/07/25
 000000610427
 Date of first issue: 2015/06/24

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements

#### Prevention:

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/eye protection/face protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

## Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/container to an approved waste disposal plant.

#### Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
_		0 - 111 - 1111 - 111 ( , 0 11 , 11 )

## SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2023/01/05

 6.0
 2024/07/25
 000000610427
 Date of first issue: 2015/06/24

Quartz (SiO2)	14808-60-7	>= 50 -< 70
Cement (chromium reduced)	65997-15-1	>= 20 -< 30
Limestone	1317-65-3	>= 1 -< 10
sulfoaluminate clinker	Not Assigned	>= 1 -< 3
calcium oxide	1305-78-8	>= 1 -< 3

#### 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause respiratory irritation.

## SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2023/01/05

 6.0
 2024/07/25
 000000610427
 Date of first issue: 2015/06/24

Notes to physician : Treat symptomatically.

#### **5. FIREFIGHTING MEASURES**

Suitable extinguishing media . Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

#### **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust.

Keep in suitable, closed containers for disposal.

### 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Sika 03

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

# SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2023/01/05

 6.0
 2024/07/25
 000000610427
 Date of first issue: 2015/06/24

products

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Observe label precautions.

Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Res- pirable dust)	0.025 mg/m3 (Silica)	TH OEL
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par- ticulate mat- ter)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par- ticulate mat- ter)	(Silica)	
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par- ticulate mat- ter)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par- ticulate mat- ter)	(Silica)	
Cement (chromium reduced)	65997-15-1	TWA (Respirable particulate matter)	1 mg/m3	ACGIH
Limestone	1317-65-3	TWA (inhala- ble dust)	15 mg/m3	TH OEL
		TWA (Respirable dust)	5 mg/m3	TH OEL
calcium oxide	1305-78-8	TWA	5 mg/m3	TH OEL
		TWA	2 mg/m3	ACGIH

## SikaGrout®-212 GP



Version 6.0

Revision Date: 2024/07/25

SDS Number: 000000610427

Date of last issue: 2023/01/05
Date of first issue: 2015/06/24

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : grey

Odour : odourless

Odour Threshold : No data available

pH : > 11

Melting point/range/Freezing

point

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

## SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2023/01/05

 6.0
 2024/07/25
 000000610427
 Date of first issue: 2015/06/24

Flammability (solid, gas) : No data available

Upper explosion limit/Upper

flammability limit

No data available

Lower explosion limit/Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : Not applicable

Solubility(ies)

Water solubility : Not applicable

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

## 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

## SikaGrout®-212 GP



Version 6.0

Revision Date: 2024/07/25

SDS Number: 000000610427

Date of last issue: 2023/01/05 Date of first issue: 2015/06/24

Hazardous decomposition

products

No hazardous decomposition products are known.

#### 11. TOXICOLOGICAL INFORMATION

#### **Acute toxicity**

Not classified due to lack of data.

#### Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

#### STOT - single exposure

May cause respiratory irritation.

### STOT - repeated exposure

Not classified due to lack of data.

#### **Aspiration toxicity**

Not classified due to lack of data.

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

No data available

## Persistence and degradability

No data available

## SikaGrout®-212 GP



Version 6.0

Revision Date: 2024/07/25

SDS Number: 000000610427

Date of last issue: 2023/01/05 Date of first issue: 2015/06/24

## **Bioaccumulative potential**

No data available

## Mobility in soil

No data available

#### Other adverse effects

**Product**:

Additional ecological infor-

mation

There is no data available for this product.

#### 13. DISPOSAL CONSIDERATIONS

**Disposal methods** 

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

## 14. TRANSPORT INFORMATION

## **International Regulations**

**UNRTDG** 

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

Environmentally hazardous : no

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

## SikaGrout®-212 GP



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2023/01/05

 6.0
 2024/07/25
 000000610427
 Date of first issue: 2015/06/24

Packing instruction (passen-

ger aircraft)

Not applicable

IMDG-Code

Not applicable **UN** number Proper shipping name Not applicable Not applicable Class Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable **EmS Code** Not applicable Marine pollutant Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Hazardous Substance Act

Conditions of restriction for the following entries should be considered:

Not applicable

Emergency Decree on Controlling the Use of Volatile

Substances

Not applicable

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

**16. OTHER INFORMATION** 

Revision Date : 2024/07/25 Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
TH OEL : Thailand. Occupational Exposure Limits

ACGIH/TWA : 8-hour, time-weighted average TH OEL/TWA : Time weighted average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service

DNEL : Derived no-effect level

# SikaGrout®-212 GP



EC50 : Half maximal effective concentration  GHS : Globally Harmonized System  IATA : International Air Transport Association  IMDG : International Maritime Code for Dangerous Goods
IATA International Air Transport Association IMDG International Maritime Code for Dangerous Goods
IATA International Air Transport Association IMDG International Maritime Code for Dangerous Goods
3
LDEO Median lethal design the amount of a material gives all at
LD50 : Median lethal dosis (the amount of a material, given all at
once, which causes the death of 50% (one half) of a group of
test animals)
LC50 : Median lethal concentration (concentrations of the chemical in
air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. TH/EN