## LANKO 452 DAMPFLEX

Revision Date: 2020/03/27

Version 2.0

SDS Number: 10000031235

### **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name Product code Type of product	<ul> <li>LANKO 452 DAMPFLEX</li> <li>100000031235</li> <li>paste</li> </ul>
Recommended use of the cl	hemical and restrictions on use
Product use	E Liquid applied membranes
Manufacturer or supplier's o	details
Company	<ul> <li>Sika (Thailand) Limited</li> <li>700/37 Moo.5 Amata Nakorn Estate</li> <li>Bangna-Trad Km.57</li> <li>Tambol Klong Tamhru</li> <li>Muang District</li> <li>Chonburi 20000</li> <li>Thailand</li> </ul>
Telephone	÷ +66 3810 9500
Emergency telephone num- ber	· +66 3821 4270-85
Telefax	: +66 3821 4286
E-mail address	Sikathai@th.sika.com

### 2. HAZARDS IDENTIFICATION

GHS Classification Skin corrosion/irritation	: Category 3
Short-term (acute) aquatic hazard	: Category 3
<b>GHS label elements</b> Hazard pictograms Signal word	: None : Warning
Hazard statements	H316 Causes mild skin irritation. H402 Harmful to aquatic life.
Precautionary statements	<ul> <li>Prevention:</li> <li>P273 Avoid release to the environment.</li> <li>Response:</li> <li>P332 + P313 If skin irritation occurs: Get medical advice/attention.</li> <li>Disposal:</li> <li>P501 Dispose of contents/container to an approved waste disposal plant.</li> </ul>

Other hazards which do not result in classification None known.

# LANKO 452 DAMPFLEX

Revision Date: 2020/03/27

Version 2.0

## SDS Number: 100000031235

#### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (%)
Limestone	1317-65-3	>= 20 - < 30
Talc (Mg3H2(SiO3)4)	14807-96-6	>= 1 - < 10
3-butoxypropan-2-ol	5131-66-8	>= 1 - < 10
titanium dioxide	13463-67-7	>= 1 - < 10
Distillates (petroleum), hydrotreated heavy naph-	64742-52-5	>= 0.1 - < 1
thenic; Baseoil —unspecified		
ammonia	1336-21-6	>= 0.25 - < 1
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one	55965-84-9	>= 0.0003 - < 0.0025
[EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-		
one [EC no. 220-239-6] (3:1) (C(M		

#### 4. FIRST AID MEASURES

General advice If inhaled	<ul> <li>No hazards which require special first aid measures.</li> <li>Move to fresh air.</li> <li>Consult a physician after significant exposure.</li> </ul>
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Flush eyes with water as a precaution.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> </ul>
If swallowed	<ul> <li>Clean mouth with water and drink afterwards plenty of water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
Most important symptoms and effects, both acute and delayed	<ul> <li>No known significant effects or hazards.</li> <li>See Section 11 for more detailed information on health effects and symptoms.</li> <li>Causes mild skin irritation.</li> </ul>
Notes to physician	: Treat symptomatically.

#### **5. FIREFIGHTING MEASURES**

Suitable extinguishing media Hazardous combustion prod- ucts	Use extinguishing measures that are appropriate cumstances and the surrounding environment. No hazardous combustion products are known	e to local cir-
Specific extinguishing meth- ods Special protective equipment for firefighters	Standard procedure for chemical fires. In the event of fire, wear self-contained breathing	g apparatus.

# LANKO 452 DAMPFLEX



Version 2.0

SDS Number: 100000031235

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	For p	ersonal protection see section 8.
Environmental precautions	If the	ot flush into surface water or sanitary sewer system. product contaminates rivers and lakes or drains inform active authorities.
Methods and materials for containment and cleaning up	Swee	in suitable, closed containers for disposal. op up or vacuum up spillage and collect in suitable con- r for disposal.

#### 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	Normal measures for preventive fire protection.
Advice on safe handling	<ul> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
Conditions for safe storage	<ul> <li>Keep container tightly closed in a dry and well-ventilated place.</li> <li>Store in accordance with local regulations.</li> </ul>

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (inhala- ble dust)	15 mg/m3	TH OEL
		TWA (Res- pirable dust)	5 mg/m3	TH OEL
Talc (Mg3H2(SiO3)4)	14807-96-6	TWA (Res- pirable dust)	2 mg/m3	TH OEL
		TWA (Res- pirable par- ticulate mat- ter)	2 mg/m3	ACGIH
titanium dioxide	13463-67-7	TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Distillates (petroleum), hy- drotreated heavy naphthenic; Baseoil – unspecified	64742-52-5	TWA (Inhala- ble particu- late matter)	5 mg/m3	ACGIH
ammonia	1336-21-6	TWA	25 ppm (Ammonia)	ACGIH

Version 2.0

# LANKO 452 DAMPFLEX

Revision Date: 2020/03/27

SDS Number: 100000031235

			STEL	35 ppm (Ammonia)	ACGIH
Personal protective equipr	ment				
Respiratory protection	:	ventilation is p that exposures The filter class imum expecte (gas/vapour/ac the product. If	s are within reco s for the respirat d contaminant c prosol/particulate	es) that may arise whe on is exceeded, self-c	nonstrates guidelines. or the max- en handling
Hand protection	:	proved standa	rd should be wo	s gloves complying w orn at all times when l sessment indicates th	nandling
Eye protection	:			h an approved standa ent indicates this is n	
Skin and body protection	:		iount of dangero	ation to its type, to the ous substances, and t	
Hygiene measures	:	Handle in accepractice. When using de When using de	ordance with go o not eat or drin o not smoke.	od industrial hygiene k. id at the end of workd	

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colour Odour Odour Threshold	::	
pH Melting point/range⊭Freezing point Boiling point/boiling range	•	
Flash point Evaporation rate	:	Not applicable No data available
Flammability	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	0Not applicable
Relative vapour density	:	No data available

# LANKO 452 DAMPFLEX



## **10. STABILITY AND REACTIVITY**

Reactivity	No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reac- tions	No hazards to be specially mentioned.
Conditions to avoid	No data available
Incompatible materials	: No data available
No decomposition if stored and	applied as directed.

#### **11. TOXICOLOGICAL INFORMATION**

#### Acute toxicity

Not classified based on available information.

#### Components:

• • •	treated heavy naphthenic; Baseoil – unspecified
Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.53 mg/l Exposure time: 4 h
	Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2,000 mg/kg

## Skin corrosion/irritation

Causes mild skin irritation.

# LANKO 452 DAMPFLEX

Version 2.0

SDS Number: 100000031235



#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

#### Components: Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil – unspecified: Toxicity to fish : LC50 (Fish): > 100 mg/l Exposure time: 96 h Toxicity to algae IC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 48 h mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1) (C(M: M-Factor (Acute aquatic tox-100 icity) : 100 M-Factor (Chronic aquatic toxicity) Persistence and degradability No data available

# Bioaccumulative potential

No data available

# Mobility in soil

No data available

# LANKO 452 DAMPFLEX



SDS Number: 100000031235

#### Other adverse effects

#### Product:

Version 2.0

Additional ecological infor-	:	There is no data available for this product.
mation		

**13. DISPOSAL CONSIDERATIONS** 

Disposal methods		
Waste from residues	The product should not be allowed to enter drains, water courses or the soil.	
	Do not contaminate ponds, waterways or ditches with chemi- cal or used container.	
	Send to a licensed waste management company.	
Contaminated packaging	Empty remaining contents.	
	Dispose of as unused product.	
	Do not re-use empty containers.	

### 14. TRANSPORT INFORMATION

#### **International Regulations**

**UNRTDG** Not regulated as a dangerous good

## IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **15. REGULATORY INFORMATION**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
Hazardous Substance Act B.E. 2535	:	Conditions of restriction for the fol- lowing entries should be considered. Not applicable
Emergency Decree on Controlling the Use of Volatile Substances B.E. 2533	:	Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

# LANKO 452 DAMPFLEX

Version 2.0

SDS Number: 100000031235

Revision Date: 2020/03/27

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3.34 %

## **16. OTHER INFORMATION**

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.