SikaBond®-T55



Version Revision Date: SDS Number: Date of last issue: 2019/01/31 2.0 2021/01/28 000000601639 Date of first issue: 2016/01/12

1. PRODUCT AND COMPANY IDENTIFICATION

Product name SikaBond®-T55

Product code 000000601639

Manufacturer or supplier's details

: Sika (Thailand) Limited Company

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000 Thailand

Telephone +66 3810 9500 : +66 3821 4270-85

Emergency telephone num-

ber

Telefax : +66 3821 4286

E-mail address Sikathai@th.sika.com

Recommended use of the chemical and restrictions on use

Product use : Adhesive

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids Category 4

Specific target organ toxicity -

repeated exposure (Inhalation)

Category 2 (Central nervous system)

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms

Signal word Warning

Hazard statements H227 Combustible liquid.

H373 May cause damage to organs (Central nervous system)

through prolonged or repeated exposure if inhaled. H412 Harmful to aquatic life with long lasting effects.

SikaBond®-T55



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/01/31

 2.0
 2021/01/28
 000000601639
 Date of first issue: 2016/01/12

Precautionary statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection/face protection.

Response:

P314 Get medical advice/ attention if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alco-

hol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container to an approved waste dis-

posal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes,	64742-82-1	>= 2.5 -< 10
cyclics, aromatics (2-25%)		
aromatic polyisocyanate	53317-61-6	>= 0.1 -< 1
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 0.1 -< 1

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

SikaBond®-T55



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/01/31

 2.0
 2021/01/28
 000000601639
 Date of first issue: 2016/01/12

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SikaBond®-T55



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/01/31

 2.0
 2021/01/28
 000000601639
 Date of first issue: 2016/01/12

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.
Observe label precautions.

Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.005 ppm	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

SikaBond®-T55



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/01/31

 2.0
 2021/01/28
 000000601639
 Date of first issue: 2016/01/12

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : light brown

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing

point Boiling point/boiling range

: No data available

Flash point : 69 °C (156 °F)

69 °C (156 °F) (Method: closed cup)

No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit/Upper

flammability limit

No data available

Lower explosion limit/Lower

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.36 g/cm3 (23 °C (73 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

SikaBond®-T55



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/01/31

 2.0
 2021/01/28
 000000601639
 Date of first issue: 2016/01/12

Partition coefficient: n-

No data available

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

aromatic polyisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 4,700 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

SikaBond®-T55



Version 2.0 Revision Date: 2021/01/28

SDS Number: 000000601639

Date of last issue: 2019/01/31 Date of first issue: 2016/01/12

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor- : An environmental hazard cannot be excluded in the event of

SikaBond®-T55



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/01/31

 2.0
 2021/01/28
 000000601639
 Date of first issue: 2016/01/12

mation unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Hazardous Substance Act

Conditions of restriction for the following entries should be considered:

Not applicable

Emergency Decree on Controlling the Use of Volatile

Not applicable

SikaBond®-T55



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/01/31

 2.0
 2021/01/28
 000000601639
 Date of first issue: 2016/01/12

Substances

Volatile organic compounds Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3.85 %

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA ACGIH Threshold Limit Values (TLV)

ACGIH/TWA : 8-hour, time-weighted average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service

DNEL : Derived no-effect level

EC50 Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of $50\% \, \text{(one half)} \, \text{of a group of}$

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

TH/EN

SVHC