LANKO 451 ROOF SEAL(SOVACRYL)



SDS Number: 100000031233 Revision Date: 2020/03/27 Version 2.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name LANKO 451 ROOF SEAL(SOVACRYL)

Product code 100000031233

Type of product paste

Recommended use of the chemical and restrictions on use

Product use : Liquid applied membranes

Manufacturer or supplier's details

Company Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000 Thailand

Telephone +66 3810 9500 Emergency telephone num-: +66 3821 4270-85

ber

Telefax

+66 3821 4286

E-mail address Sikathai@th.sika.com

2. HAZARDS IDENTIFICATION

GHS Classification

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms None Signal word : None

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/container to an approved waste dis-

posal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

LANKO 451 ROOF SEAL(SOVACRYL)



SDS Number: 100000031233 Revision Date: 2020/03/27 Version 2.0

Substance / Mixture Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Limestone	1317-65-3	>= 30 - < 50
Distillates (petroleum), hydrotreated heavy naph-	64742-52-5	>= 1 -< 10
thenic; Baseoil – unspecified		
ammonia	1336-21-6	>= 0.25 -<1
diuron (ISO)	330-54-1	>= 0.025 - < 0.1
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M	55965-84-9	>= 0.0003 - < 0.0025

4. FIRST AID MEASURES

General advice No hazards which require special first aid measures.

If inhaled Move to fresh air.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Notes to physician Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : For personal protection see section 8.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

LANKO 451 ROOF SEAL(SOVACRYL)



Version 2.0 SDS Number: 100000031233 Revision Date: 2020/03/27

respective authorities.

Methods and materials for containment and cleaning up

Keep in suitable, closed containers for disposal.

Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
Limestone	1317-65-3	TWA (inhala-	15 mg/m3	TH OEL
		ble dust)		
		TWA(Res-	5 mg/m3	TH OEL
		pirable dust		
Distillates (petroleum), hy-	64742-52-5	TWA (Inhala-	5 mg/m3	ACGIH
drotreated heavy naphthenic; Baseoil – unspecified		ble particu- late matter		
ammonia	1336-21-6	TWA	25 ppm (Ammonia)	ACGIH
		STEL	35 ppm (Ammonia)	ACGIH
diuron (ISO)	330-54-1	TWA	10 mg/m3	TH OEL

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

LANKO 451 ROOF SEAL(SOVACRYL)



Version 2.0 SDS Number: 100000031233 Revision Date: 2020/03/27

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : various

Odour : characteristic

Odour Threshold : No data available

pH : ca.9

Melting point/range / Freezing

point

. No data available

Boiling point/boiling range No data available

Flash point : Not applicable Evaporation rate : No data available

Flammability : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0Not applicable

Relative vapour density : No data available

Density : ca. 1.35 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

LANKO 451 ROOF SEAL(SOVACRYL)



Version 2.0 SDS Number: 100000031233 Revision Date: 2020/03/27

Explosive properties : No data available

Molecular weight : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- : No hazards to be specially mentioned.

tions

Conditions to avoid : No data available Incompatible materials : No data available No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

LANKO 451 ROOF SEAL(SOVACRYL)



Version 2.0 SDS Number: 100000031233 Revision Date: 2020/03/27

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to algae : IC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 48 h

diuron (ISO):

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic : 10

toxicity)

 $mixture\ of;\ 5\text{-chloro-2-methyl-4-isothiazolin-3-one}\ | EC\ no.\ 247\text{-}500\text{-}7]\ and\ 2\text{-methyl-2H-isothiazolin-3-one}\ | EC\ no.\ 247\text{-}500\text{-}7]\ and\ 2\text{-}500\text{-}7]\ and\ 2\text{-}500\text{-}7]\ and\ 2\text{-}500\text{-}7]\ and\ 2\text{-}500\text{-}7]\ and\ 2\text{-}500\text{-}7]\ and\ 2\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text{-}700\text$

isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M:

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 100

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

LANKO 451 ROOF SEAL(SOVACRYL)



Version 2.0 SDS Number: 100000031233 Revision Date: 2020/03/27

courses or the soil.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Hazardous Substance Act B.E. 2535

Conditions of restriction for the following entries should be considered:

Not applicable

Emergency Decree on Controlling the Use of Volatile

Substances B.E. 2533

Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 1.51 %

16. OTHER INFORMATION

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.