SikaTile®-640 TG Thin Gap



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/11/24

 4.0
 2024/05/30
 100000031482
 Date of first issue: 2020/03/25

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaTile®-640 TG Thin Gap

Manufacturer or supplier's details

Company : Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000

Thailand

Telephone : +66 3810 9500

Emergency telephone number : +66 3821 4270-85

E-mail address : Sikathai@th.sika.com

Telefax : +66 3821 4286

Recommended use of the chemical and restrictions on use

Product use : Cement / Mortar

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation : Category 1

Specific target organ toxicity - :

single exposure

Category 3 (Respiratory system)

GHS label elements

Hazard pictograms





Signal word : Danger

SikaTile®-640 TG Thin Gap



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/11/24

 4.0
 2024/05/30
 100000031482
 Date of first issue: 2020/03/25

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements

Prevention:

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/eye protection/face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
0.10111100111110	O, 10 110.	00110011111411011 (/0 11/11/)

SikaTile®-640 TG Thin Gap



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/11/24

 4.0
 2024/05/30
 100000031482
 Date of first issue: 2020/03/25

Limestone	1317-65-3	>= 30 -< 50
Cement, portland, chemicals	65997-15-1	>= 30 -< 50
calcium sulfate	7778-18-9	>= 10 -< 20
terbutryn	886-50-0	>= 0.0003 -< 0.0025

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage. May cause respiratory irritation.

Notes to physician : Treat symptomatically.

SikaTile®-640 TG Thin Gap



Version 4.0

Revision Date: 2024/05/30

SDS Number: 100000031482 Date of last issue: 2022/11/24 Date of first issue 2020/03/25

5. FIREFIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod-

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust.

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Do not breathe vapours/dust.

SikaTile®-640 TG Thin Gap



Version Revision Date: SDS Number: Date of last issue: 2022/11/24 4.0 2024/05/30 100000031482 Date of first issue: 2020/03/25

Conditions for safe storage Store in original container.

> Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Further information on stor-

Keep in a dry place.

age stability No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
Limestone	1317-65-3	TWA (inhala-	15 mg/m3	TH OEL
		ble dust)		
		TWA (Res-	5 mg/m3	TH OEL
		pirable dust		
Cement, portland, chemicals	65997-15-1	TWA (Res-	1 mg/m3	ACGIH
		pirable par-		
		ticulate mat- ter		
calcium sulfate	7778-18-9	TWA (Inhala-	10 mg/m3	ACGIH
		ble particu- late matter	(Calcium)	
terbutryn	886-50-0	TWA (Inhala-	2 mg/m3	ACGIH
		ble particu- late matter		

Personal protective equipment

Respiratory protection Use respiratory protection unless adequate local exhaust

> ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection Chemical-resistant, impervious gloves complying with an

> approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

SikaTile®-640 TG Thin Gap



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/11/24

 4.0
 2024/05/30
 100000031482
 Date of first issue: 2020/03/25

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : various

Odour : odourless

Odour Threshold : No data available

pH : > 11

Melting point/range / Freezing

point

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit/Upper

flammability limit

No data available

Lower explosion limit/Lower

flammability limit

No data available

Vapour pressure : Not applicable

Relative vapour density : No data available

Density : ca. 0.9 - 1.0 g/cm 3 (25 °C (77 °F))

Solubility(ies)

SikaTile®-640 TG Thin Gap



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/11/24

 4.0
 2024/05/30
 100000031482
 Date of first issue: 2020/03/25

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

calcium sulfate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

SikaTile®-640 TG Thin Gap



Version 4.0

Revision Date: 2024/05/30

SDS Number: 100000031482

Date of last issue: 2022/11/24 Date of first issue: 2020/03/25

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

terbutryn:

M-Factor (Acute aquatic tox- : 100

icitv)

M-Factor (Chronic aquatic : 100

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

SikaTile®-640 TG Thin Gap



Version Revision Date: 4.0 2024/05/30

SDS Number: 100000031482

Date of last issue: 2022/11/24 Date of first issue: 2020/03/25

Other adverse effects

Product:

Additional ecological infor-

mation

There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen-

ger aircraft)

Not applicable

IMDG-Code

UN number : Not applicable Proper shipping name : Not applicable

SikaTile®-640 TG Thin Gap



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2022/11/24

 4.0
 2024/05/30
 100000031482
 Date of first issue: 2020/03/25

Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Hazardous Substance Act : Conditions of restriction for the fol-

lowing entries should be considered:

Not applicable

Emergency Decree on Controlling the Use of Volatile

Substances

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

Not applicable

16. OTHER INFORMATION

Revision Date : 2024/05/30 Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
TH OEL : Thailand. Occupational Exposure Limits

ACGIH/TWA : 8-hour, time-weighted average TH OEL/TWA : Time weighted average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

SikaTile®-640 TG Thin Gap



Version 4.0	Revision Date: 2024/05/30		SDS Number: 100000031482	Date of last issue: 2022/11/24 Date of first issue: 2020/03/25	
IAT	A	:	International Air Transport As	sociation	
IME)G	:	International Maritime Code for Dangerous Goods		
LD	50	:	Median lethal dosis (the amou once, which causes the death test animals)	of 50% (one half) of a group of	
LC	50	:	Median lethal concentration (c air that kills 50% of the test ani period)	concentrations of the chemical in mals during the observation	
MA	RPOL	:	International Convention for the Ships, 1973 as modified by the	ne Prevention of Pollution from e Protocol of 1978	
OE	L	:	Occupational Exposure Limit		
PB ⁻	Γ	:	Persistent, bioaccumulative and toxic		
PNI	EC	:	Predicted no effect concentration		
RE.	ACH	:	_		
SVI	HC	:	Substances of Very High Concern		
vPv	'B	:	Very persistent and very bioac	ccumulative	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. TH / EN