



Davco

BUILDING TRUST



PRODUCT DATA SHEET

Davco EASY FIX

READY TO USE TILE ADHESIVE

DESCRIPTION

Davco EASY FIX is a ready to use tile adhesive.

USES

- Interior
- General tiles onto various substrates
- Tile on tile

CHARACTERISTICS / ADVANTAGES

- Ideal for repairing jobs
- High bonding strength
- Fast setting and easy to use
- Flexible

PRODUCT INFORMATION

Packaging	5 kg. pail
Shelf life	12 months from date of production if stored properly in undamaged original sealed packaging.
Storage conditions	Store in dry conditions and protected from direct sunlight.
Density	1.4 - 1.5 kg./L
pH-Value	8 - 10

TECHNICAL INFORMATION

Tensile adhesion strength	Initial	> 1 MPa
	Heat aging	> 1 MPa
	Open time bonding after 20 minutes	≥ 0.5 MPa

APPLICATION INFORMATION

Ambient air temperature	min. +5°C - max. +35°C
Open Time	25 - 30 minutes (at 25°C)
Adjustability time	25 - 30 minutes (at 25°C)

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

- Surface must be clean and without any trace of oil.
- New concrete must be allowed to cure for at least 28 days.
- New render must be allowed to cure for at least 7 days.

MIXING

- Ready-to-use paste. No water must be added.
- Stir the product before applying.

APPLICATION

- Spread the product by using notched side of trowel onto prepared surface.
- In case of tile that have uneven, lug or groove back, coat the back of tile with DAVCO EASY FIX.
- Press the tile firmly into the position.
- Clean the excessive adhesive and wait for 24 hours before applying tile grout.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Thailand) Limited
700/37 Moo 5 Amata City Chonburi
Industrial Estate, T. Klong Tamhru
A. Muang, Chonburi 20000, Thailand
Tel : +66 3810 9500
E-mail : sikathai@th.sika.com
Website: tha.sika.com



Product Data Sheet
Davco EASY FIX
October 2020, Version 01.01
02171020000000036

DavcoEASYFIX-en-THDAVCO-(10-2020)-1-1.pdf