



**BUILDING TRUST**



## PRODUCT DATA SHEET

# DAVCO® Granito PLUS

PREPACKED STANDARD CEMENTITIOUS TILE ADHESIVE



TIS. 2703-2559

### DESCRIPTION

DAVCO® Granito PLUS is a standard cement-based tile adhesive with polymer-modified as a single component, pre-packed tiling adhesive mortar combining cement with selected grades of sand and several admixtures. Only requires the addition of water.

### USES

- Perfect for granito tiles up to 60x60 cm on both interior floor and wall installation.
- Can be used for large size of granito exterior floor installation only.
- For General ceramic tile. Both interior and exterior floor and wall installation.
- Substrates: Cement. Also suitable for tiling onto waterproof membranes in wet areas.

### CHARACTERISTICS / ADVANTAGES

- Dedicated to granito and low porous tiles
- Excellent bonding strength
- Extended open time resulting in faster application
- Tile can be adjusted after laying within 15 minutes
- Smooth and easy to use
- LEED V4.1 Confirmation: Low VOCs

### SUSTAINABILITY

- LEED v4 and v4.1 BETA
- WELL Building Standard

### APPROVALS / CERTIFICATES

- EN 12004 C1TE
- ANSI 118.1
- TIS 2703-2559

### PRODUCT INFORMATION

Composition	Hydraulic binder, mineral filler, polymer and admixtures
Packaging	20 kg/ bag
Shelf life	12 months from date of production if stored in undamaged and unopened, original sealed packaging.
Storage conditions	Store in dry condition and protected from direct sunshine.
Appearance and colour	Grey powder
Density	1.3 ± 0.1 kg/L
pH-Value	12 ± 1

## TECHNICAL INFORMATION

<b>Tensile adhesion strength</b>	<b>At 28 days</b>		(EN 12004) (ISO 13007)
	Initial	≥ 0.5 MPa	
	Water immersion	≥ 0.5 MPa	
	Heat aging	≥ 0.5 MPa	
	Open time bonding after 20 min	≥ 0.5 MPa	
<b>Shear adhesion strength</b>	<b>Glazed Wall Tile</b>		(ANSI 118.1)
	7 days	≥ 1.38 MPa	
	7 days water immersion	≥ 1.03 MPa	
	<b>Porcelain Mosaic Tile</b>		(ANSI 118.1)
	1 day	≥ 0.34 MPa	
	7 days	≥ 1.03 MPa	
	7 days water immersion	≥ 0.69 MPa	
	28 days	≥ 1.03 MPa	
	12 weeks	≥ 1.03 MPa	

## APPLICATION INFORMATION

<b>Mixing ratio</b>	Approx. 4.8 to 5.6 litre water per bag 20 kg			
<b>Consumption</b>	<b>Trowel size</b>	<b>Size of tile (cm x cm)</b>	<b>Surface of tile (cm<sup>2</sup>)</b>	<b>Consumption (20 kg)</b>
	3 mm	2.5 x 2.5	6.25	7 - 8 m <sup>2</sup>
		5.0 x 5.0	25	
	6 mm	10 x 10	100	5 - 6 m <sup>2</sup>
		20 x 20	400	
		20 x 25	500	
		30 x 30	900	
	9 mm	40 x 40	1600	2 - 3 m <sup>2</sup>
		50 x 50	2500	
		60 x 60	3600	
> 60 x 60		> 3600		
<p>Note:</p> <p>1. This is an average calculation. Actual usage may differ from the estimate. Due to the different surface conditions. Surface absorption and the purpose of the individual's use.</p> <p>2. For tile size more than 40 cm x 40 cm should apply tile adhesive on the surface and a very thin layer on the back of tile.</p>				
<b>Ambient air temperature</b>	+5°C to +35°C			
<b>Pot Life</b>	180 - 240 minutes (at 25°C)			
<b>Open Time</b>	20 - 25 minutes (at 25°C)			
<b>Adjustability time</b>	15 - 20 minutes (at 25°C)			
<b>Applied product ready for use</b>	~ 24 hours			

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## IMPORTANT CONSIDERATIONS

- Maximum weight of tile for interior/ exterior wall application is 30 kg/ m<sup>2</sup>.
- Use a proper notched trowel to spread the adhesive onto the substrate with the flat side of the trowel until it is smooth.
- Use the notched side of the trowel to create an even adhesive bed. minimum bed thickness is 2 mm. for wall and 3 mm. for floor (size depends on the thickness of tiles)
- Ensure the adhesive is wet when the tiles are laid and tapped into the position to ensure full contact with the adhesive. Do not spread more than 1 sqm at once.
- Once the tiles have been laid, leave to stand for 24 hours or the tile adhesive is dry before grouting with DAVCO Tile Grout.
- Refer to the Safety Data Sheet.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

- Substrate should be sound, clean and without any trace of oil. The level should be considered.
- Painted surfaces must be abraded to expose at least 80% of the original substrate.
- New concrete must be allowed to cure at least 28 days.
- New render must be allowed to cure at least 7 days per 1 cm thickness.
- Damp the substrate to decrease water absorption before tiling.

## MIXING

- Mix DAVCO® Granito PLUS 20 kg with 4.8 - 5.6 Litres of clean water by electrical mixer until the compound is evenly distributed.
- Allow the mixture to stand for 2 - 3 minutes for good reaction and reducing air bubble before using the adhesive.

## APPLICATION

- Spread tile adhesive by using notched trowel onto substrate.
- Fix tile on tile adhesive and knocked over with rubber hammer.
- The dual bonding will be applied when size of tile is over than 25 cm x 25 cm. Applying thin layer of tile adhesive onto a back of tile, then fix the tile on tile adhesive substrate.
- Once the tiles have been laid, leave to stand for 24 hours or the tile adhesive is dry before grouting with DAVCO Tile Grout

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika (Thailand) Limited

700/37 Moo 5 Amata City Chonburi  
Industrial Estate, T. Klong Tamhru  
A. Muang, Chonburi 20000, Thailand  
Tel : +66 3810 9500  
E-mail : sikathai@th.sika.com  
Website: tha.sika.com



### Product Data Sheet

DAVCO® Granito PLUS  
July 2022, Version 04.02  
021710102000000618

DAVCOGranitoPLUS-en-THDAVCO-(07-2022)-4-2.pdf