

PRODUCT DATA SHEET

Sika® Plastocrete®-850 WP

Waterproofing Admixture for Concrete

DESCRIPTION

A concrete / mortar admixture in liquid form that acts both as a plasticizer and waterproofing compound.

USES

Sika® Plastocrete®-850 WP is recommended for use in waterproofing of masonry and concrete structures such as:

- Sloped & Flat Roof Slabs
- Slab on Ground
- Beams
- Swimming Pools
- Water Tanks

wherever waterproof concrete and plaster is required.

CHARACTERISTICS / ADVANTAGES

Sika® Plastocrete®-850 WP provides the following properties:

- Improved workability without increased water content
- Allows easier compaction leading to denser concrete and superior finish
- Increased strength and durability
- Reduced shrinkage
- Improved watertightness
- Increased cohesiveness of mortar

APPROVALS / CERTIFICATES

Complies with ASTM. C 494-81 Type A & D

PRODUCT INFORMATION

Composition	Modified Lignosulphonate
Packaging	200 liter/ Drum 1 liter, 5 liter, 25 liter/ Pail
Appearance / Colour	Brown
Shelf life	12 months from the date of production If stored properly in undamaged, original, sealed packaging.
Storage conditions	Store at protected area from direct sunlight at temperature between 5°C and 40°C
Density	1.125 - 1.145 kg/l (at temperature 25°C)
pH-Value	4.0 - 6.0

APPLICATION INFORMATION

Recommended dosage	Typical dosage 1,000 CC. per 100 kg. of cement weight. Sika® Plastocrete®-850 WP is compatible with all types of Portland cement including S.R.C.
Dispensing	Sika® Plastocrete®-850 WP should be dispensed directly into the mixing water, prior to its addition to the aggregates. Where overdosing accidentally occurs, apart from retardation of the initial set, no detrimental effect will take place.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

IMPORTANT CONSIDERATIONS

Accidental overdosing of Sika® Plastocrete®-850 WP causes an extension of the initial setting time. In the case of overdosing do not disturb the concrete. Ensure the concrete is properly cured. Consult Sika's Technical Department.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Thailand) Limited
700/37 Moo 5 Amata City Chonburi
Industrial Estate, T. Klong Tamhru
A. Muang, Chonburi 20000, Thailand
Tel : +66 3810 9500
E-mail : sikathai@th.sika.com
Website: tha.sika.com



Product Data Sheet
Sika® Plastocrete®-850 WP
January 2020, Version 01.02
021303011000000723

SikaPlastocrete-850WP-en-TH-(01-2020)-1-2.pdf

