# Sikafloor®-31 PurCem® LP Part C



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/12/23

 2.0
 2021/11/25
 100000030097
 Date of first issue: 2019/12/23

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-31 PurCem® LP Part C

Product code : 100000030097

Manufacturer or supplier's details

Company : Sika (Thailand) Limited

700/37 Moo. 5 Amata Nakorn Estate

Bangna-Trad Km.57 Tambol Klong Tamhru

Muang District Chonburi 20000 Thailand

Telephone : +66 3810 9500 Emergency telephone num- : +66 3821 4270-85

ber

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

Recommended use of the chemical and restrictions on use

Product use : Polyurethane coating

### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 1

Specific target organ toxicity -

single exposure

Category 3 (Respiratory system)

**GHS** label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

# Sikafloor®-31 PurCem® LP Part C



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/12/23

 2.0
 2021/11/25
 100000030097
 Date of first issue: 2019/12/23

Precautionary statements

#### Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection/face protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P362 Take off contaminated clothing and wash before reuse.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

## Other hazards which do not result in classification

None known.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

## Components

Chemical name	CAS-No.	Concentration (% w/w)
Cement (chromium reduced)	65997-15-1	>= 90 -<= 100
calcium dihydroxide	1305-62-0	>= 3 -< 10

## 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

# Sikafloor®-31 PurCem® LP Part C



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/12/23

 2.0
 2021/11/25
 100000030097
 Date of first issue: 2019/12/23

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects

Cough

Respiratory disorder Excessive lachrymation

**Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms.

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

Notes to physician : Treat symptomatically.

## **5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Specific extinguishing meth-

. ods Standard procedure for chemical fires.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

# Sikafloor®-31 PurCem® LP Part C



Version 2.0

Revision Date: 2021/11/25

SDS Number: 100000030097 Date of last issue 2019/12/23 Date of first issue: 2019/12/23

for firefighters

### **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emergency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Try to prevent the material from entering drains or water **Environmental precautions** 

courses.

No special environmental precautions required.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

### 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	

# Sikafloor®-31 PurCem® LP Part C



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/12/23

 2.0
 2021/11/25
 100000030097
 Date of first issue: 2019/12/23

Cement (chromium reduced)	65997-15-1	TWA (Respirable particulate matter)	1 mg/m3	ACGIH
calcium dihydroxide	1305-62-0	TWA (inhala- ble dust)	15 mg/m3	TH OEL
		TWA (Respirable dust)	5 mg/m3	TH OEL
		TWA	5 mg/m3	ACGIH

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : white

Odour : No data available

Odour Threshold : No data available

# Sikafloor®-31 PurCem® LP Part C



Version Revision Date: SDS Number: Date of last issue: 2019/12/23 2.0 2021/11/25 10000030097 Date of first issue: 2019/12/23

No data available

Not applicable

рΗ No data available

Melting point/range / Freezing

Flash point

Boiling point/boiling range No data available

Evaporation rate No data available

Flammability (solid, gas)

Upper explosion limit/Upper

flammability limit

No data available

No data available

Lower explosion limit/Lower

flammability limit

No data available

No data available Vapour pressure

Relative vapour density No data available

No data available Density

Bulk density

ca. 1,500 kg/m3

Solubility(ies)

Water solubility No data available

Solubility in other solvents No data available

Partition coefficient: n-

No data available

octanol/water

Auto-ignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic Not applicable

Viscosity, kinematic No data available

Explosive properties No data available

No data available Oxidizing properties

## 10. STABILITY AND REACTIVITY

No dangerous reaction known under conditions of normal use. Reactivity

# Sikafloor®-31 PurCem® LP Part C



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/12/23

 2.0
 2021/11/25
 100000030097
 Date of first issue: 2019/12/23

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

#### 11. TOXICOLOGICAL INFORMATION

## **Acute toxicity**

Not classified based on available information.

#### Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye damage.

## Respiratory or skin sensitisation

## Skin sensitisation

Not classified based on available information.

## Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

## STOT - single exposure

May cause respiratory irritation.

## STOT - repeated exposure

Not classified based on available information.

# **Aspiration toxicity**

Not classified based on available information.

# Sikafloor®-31 PurCem® LP Part C



Version 2.0

Revision Date: 2021/11/25

SDS Number: 100000030097

Date of last issue: 2019/12/23 Date of first issue: 2019/12/23

#### 12 ECOLOGICAL INFORMATION

## **Ecotoxicity**

No data available

# Persistence and degradability

No data available

# **Bioaccumulative potential**

No data available

### Mobility in soil

No data available

#### Other adverse effects

# Product:

Additional ecological infor-

mation

There is no data available for this product.

## 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

# 14. TRANSPORT INFORMATION

# International Regulations

### **UNRTDG**

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# Sikafloor®-31 PurCem® LP Part C



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 2019/12/23

 2.0
 2021/11/25
 100000030097
 Date of first issue: 2019/12/23

#### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Hazardous Substance Act : Conditions of restriction for the fol-

lowing entries should be considered.

Not applicable

Emergency Decree on Controlling the Use of Volatile

Not applicable

Substances

International Chemical Weapons Convention (CWC)

Not applicable

Schedules of Toxic Chemicals and Precursors

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

Not applicable

#### **16. OTHER INFORMATION**

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
TH OEL : Thailand. Occupational Exposure Limits

ACGIH/TWA : 8-hour, time-weighted average

TH OEL/TWA : Time weighted average

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service

DNEL : Derived no effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

# Sikafloor®-31 PurCem® LP Part C



Version Revision Date: SDS Number: Date of last issue: 2019/12/23 2.0 2021/11/25 10000030097 Date of first issue: 2019/12/23

**REACH** Regulation (EC) No 1907/2006 of the European Parliament and

> of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals

(REACH), establishing a European Chemicals Agency

**SVHC** Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication All warranties are excluded Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

TH/EN