

## PRODUCT DATA SHEET

## Sika® Thinner C

Solvent based thinner and cleaner

**DESCRIPTION**

Sika® Thinner C is a solvent blend used in combination with epoxy or polyurethane based products and membranes.

**USES**

Recommended applications include:

- Component of priming systems
- Modification of membrane viscosity
- Cleaning of application equipment
- Re-activation of over-exposed membranes

**CHARACTERISTICS / ADVANTAGES****PRODUCT INFORMATION**

<b>Composition</b>	Blend of organic solvents
<b>Packaging</b>	3 L / 25 L
<b>Shelf life</b>	60 months
<b>Storage conditions</b>	Always store closed containers in cool, ventilated and dry location, away from heat and oxidizing agents. Do not store in direct sunlight or in temperatures below 5 °C or above 35 °C.
<b>Appearance and colour</b>	Clear / colourless liquid
<b>Density</b>	ca. 0.86 g/cm <sup>3</sup>
<b>Flash point</b>	ca. 24 °C

**BASIS OF PRODUCT DATA**

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

**ECOLOGY, HEALTH AND SAFETY****REGULATION (EC) NO 1907/2006 - REACH**

For information and advice on the safe handling, stor-

age and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

Follow instructions for the product being thinned.  
Cleaning: take care as product is flammable. Apply using a clean cloth which should be disposed of in line with local regulations.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika (Thailand) Limited

700/37 Moo 5 Amata City Chonburi  
Industrial Estate, T. Klong Tamhru  
A. Muang, Chonburi 20000, Thailand  
Tel : +66 3810 9500  
E-mail : sikathai@th.sika.com  
Website: tha.sika.com



### Product Data Sheet

Sika® Thinner C  
January 2023, Version 02.01  
020611040010000006

SikaThinnerC-en-TH-(01-2023)-2-1.pdf