

PRODUCT DATA SHEET

SikaWall®-720 E

Ready-to-use 2-in-1 wall repair cream for interior wall skim coating and crack filling

DESCRIPTION

SikaWall®-720 E is a ready-to-use, acrylic-based 2-in-1 wall repair cream for interior applications. It is designed for interior skim coating and crack filling, providing a smooth, paint-ready finish.

USES

- Interior wall repairs
- Filling small cracks
- Repairing nail holes and small holes
- Smoothing uneven and rough wall surfaces
- Skim coating before painting
- Repairing peeling paint areas

FEATURES

- Ready to use
- Fast drying
- Excellent adhesion
- Low shrinkage
- Easy application
- Easy to sand
- White colour blends well under paint

PRODUCT INFORMATION

Packaging	250g/tube, 45 tubes/carton box
Appearance and colour	White paste
Shelf life	12 months from the date of production if stored in undamaged and unopened, original sealed packaging
Storage conditions	Store in a dry place at temperatures between +5°C and +25°C. Protect from direct sunlight.
pH-Value	11

TECHNICAL INFORMATION

Tensile adhesion strength	0.4Mpa
Flexural toughness	100mm Round bar

APPLICATION INFORMATION

Layer thickness	0.5 to 1.0 mm per coat, and should not exceed 1 mm in a single coat.
Waiting time to overcoating	~24 hours

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- The working temperature is 5-30°C
- The coating thickness should not exceed 0.5-1 mm (1 coat)
- Do not apply to damp substrate.
- Do not add any water or other product.
- Not suitable for movement joints.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage, and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological, and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

The surface must be clean, dry, and free of dust, oil, paint, and other contamination. Remove all excess seams or edges mechanically to level the surface.

MIXING

SikaWall®-720 E is supplied ready to use - no water or other mixing is added.

APPLICATION METHOD / TOOLS

1. Fill in cracks with SikaWall®-720 E using a knife
2. Apply a thin skim coat over the repaired area to feather the edges.
3. Allow the first coat to dry for at least 20 minutes before applying the second coat.
4. Apply finishing coat with a trowel; use sandpaper and a sanding block to obtain a smooth surface.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Thailand) Limited

700/37 Moo 5 Amata City Chonburi
Industrial Estate, T. Klong Tamhru
A. Muang, Chonburi 20000, Thailand
Tel : +66 3810 9500
E-mail : sikathai@th.sika.com
Website: tha.sika.com



Product Data Sheet

SikaWall®-720 E

August 2026, Version 01.01
021840303000000045

SikaWall-720E-en-TH-(08-2026)-1-1.pdf