



BUILDING TRUST



## PRODUCT DATA SHEET

# LANKO 113 PATCH

### THIN RENDERING MORTAR FOR SMOOTH FINISHING

#### DESCRIPTION

LANKO 113 PATCH is a one component, ready-mixed powder for leveling and smoothing uneven surface of wall and ceiling.

#### USES

LANKO 113 PATCH is used as an underlay before skim coating on concrete, mortar, brick and block. Lanko 113 PATCH is a cosmetic mortar designed to eliminate surface defects 3-10 mm on

- Fair-face concrete
- Precast concrete panels
- Columns and beams
- Block works

#### CHARACTERISTICS / ADVANTAGES

LANKO 113 PATCH provides similar finishing with normal rendering and compatible with decorative wall-covering.

- Easy to use and apply, just add water
- Interior and exterior application
- Can be exposed or covered by other materials
- Smooth finished result as normal rendering with grey color
- Compatible with decorative wall covering
- Good adhesion

#### PRODUCT INFORMATION

Composition	Cementitious and polymer modified powder
Packaging	25 kg/bag
Appearance / Colour	Grey powder
Shelf life	12 months from date of production if stored in undamaged and unopened, original sealed packaging.
Storage conditions	Store in dry condition and protected from direct sunshine
Density	1.4 - 1.5 kg/L
Maximum grain size	0.5 mm
pH-Value	~ 12

#### TECHNICAL INFORMATION

Tensile adhesion strength	> 0.75 MPa at 28 days
---------------------------	-----------------------

#### APPLICATION INFORMATION

Mixing ratio	Approx. 5.25 to 5.50 litre water per bag 25 kg
--------------	--

PRODUCT DATA SHEET  
LANKO 113 PATCH  
August 2020, Version 01.01  
02182010100000009

<b>Consumption</b>	Approx. 1.3 kg/m <sup>2</sup> per 1 mm thickness
<b>Layer thickness</b>	3 - 10 mm
<b>Ambient air temperature</b>	+5°C to +35°C
<b>Pot Life</b>	Approx. 150 minutes (at 25°C)
<b>Initial set time</b>	Approx. 3 hours (at 25°C)
<b>Waiting time to overcoating</b>	~7 days

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

1. Surface must be clean, dry, and free of dust, oil, paint.
2. Damage concrete, seams and rock pockets exceeding 3 mm. must be treated prior to application.
3. New concrete must be dried 3-7 days depend on weather condition before application.
4. Damp the surface before application.

### MIXING

1. Mix LANKO 113 PATCH 25 kg. bag with 5.25–5.50 litre of clean water (21-22% of mortar) until the product is evenly distributed.
2. Use mixing machine mix at low speed not over than 500 RPM.
3. Mixing time: at least 3 minutes and required consistency is obtained.
4. Leave to stand for 1-3 minutes.
5. Do not add water after mixing.

### APPLICATION

1. Apply the first coat with a trowel.
2. Allow a sufficient drying time 3-4 hours so that it is not drawn off while applying 2<sup>nd</sup> coat.
3. Use a sponge to rub the surface in a circle motion for smooth finishing.
4. Allow a minimum of 7 days curing before applying a covering material.

## IMPORTANT CONSIDERATIONS

- Do not apply on gypsum substrate.
- Protect for 24 hours in case of heavy rain or direct sun.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

**Sika (Thailand) Limited**  
 700/37 Moo 5 Amata City Chonburi  
 Industrial Estate, T. Klong Tamhru  
 A. Muang, Chonburi 20000, Thailand  
 Tel : +66 3810 9500  
 E-mail : sikathai@th.sika.com  
 Website: tha.sika.com



**PRODUCT DATA SHEET**  
**LANKO 113 PATCH**  
 August 2020, Version 01.01  
 021820101000000009

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

LANKO113PATCH-en-THLANKO-(08-2020)-1-1.pdf