

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version
3.0

Revision Date:
2022/02/25

SDS Number:
100000003307

Date of last issue: 2020/11/14
Date of first issue: 2018/05/24

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaPower®-4720 Part B

Product code : 100000003307

Manufacturer or supplier's details

Company : Sika (Thailand) Limited
700/37 Moo. 5 Amata Nakorn Estate
Bangna-Trad Km.57
Tambol Klong Tamhru
Muang District
Chonburi 20000
Thailand

Telephone : +66 3810 9500

Emergency telephone number : +66 3821 4270-85

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

Recommended use of the chemical and restrictions on use

Product use : Adhesive

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 1

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version
3.0

Revision Date:
2022/02/25

SDS Number:
100000003307

Date of last issue: 2020/11/14
Date of first issue: 2018/05/24

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|------------|-----------------------|
| 3,3'-oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | >= 10 -< 20 |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | >= 5 -< 10 |
| 2-ethyl-4-methylimidazole | 931-36-2 | >= 1 -< 3 |
| 2-methylpentane-1,5-diamine | 15520-10-2 | >= 1 -< 3 |
| bis(dimethylamino)methylphenol | 71074-89-0 | >= 1 -< 3 |

SAFETY DATA SHEET

SikaPower®-4720 Part B



| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 3.0 | Revision Date: 2022/02/25 | SDS Number: 100000003307 | Date of last issue: 2020/11/14 Date of first issue: 2018/05/24 |
|----------------|------------------------------|-----------------------------|---|

| | | |
|-------------------|----------|-------------|
| 4-methylimidazole | 822-36-6 | >= 0.1 -< 1 |
|-------------------|----------|-------------|

4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.
corrosive effects
sensitising effects
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns.
- Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

SAFETY DATA SHEET

SikaPower®-4720 Part B



| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 3.0 | Revision Date: 2022/02/25 | SDS Number: 100000003307 | Date of last issue: 2020/11/14 Date of first issue: 2018/05/24 |
|----------------|------------------------------|-----------------------------|---|

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
-

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and
-

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version
3.0

Revision Date:
2022/02/25

SDS Number:
10000003307

Date of last issue: 2020/11/14
Date of first issue: 2018/05/24

kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous liquid
- Colour : beige
- Odour : amine-like
- Odour Threshold : No data available

SAFETY DATA SHEET

SikaPower®-4720 Part B



| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 3.0 | Revision Date: 2022/02/25 | SDS Number: 100000003307 | Date of last issue: 2020/11/14 Date of first issue: 2018/05/24 |
|----------------|------------------------------|-----------------------------|---|

| | | |
|---|---|--|
| pH | : | Not applicable substance/mixture is non-soluble (in water) |
| Melting point/range /Freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flash point | : | > 93.4 °C (200.1 °F) (Method: closed cup) |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit /Upper flammability limit | : | No data available |
| Lower explosion limit /Lower flammability limit | : | No data available |
| Vapour pressure | : | 0.0133322 hPa |
| Relative vapour density | : | No data available |
| Density | : | 1.13 g/cm ³ (20 °C (68 °F)) |
| Solubility(ies) | : | |
| Water solubility | : | insoluble |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | : | |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | > 10000 mm ² /s (40 °C (104 °F)) |
| Explosive properties | : | No data available |
| Oxidizing properties | : | No data available |

10. STABILITY AND REACTIVITY

| | | |
|------------|---|---|
| Reactivity | : | No dangerous reaction known under conditions of normal use. |
|------------|---|---|

SAFETY DATA SHEET

SikaPower®-4720 Part B



| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 3.0 | Revision Date: 2022/02/25 | SDS Number: 100000003307 | Date of last issue: 2020/11/14 Date of first issue: 2018/05/24 |
|----------------|------------------------------|-----------------------------|---|

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

3,3'-oxybis(ethyleneoxy)bis(propylamine):

Acute oral toxicity : LD50 Oral (Rat): ca. 3,560 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,500 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

2-methylpentane-1,5-diamine:

Acute oral toxicity : LD50 Oral (Rat): 1,170 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,870 mg/kg

4-methylimidazole:

Acute oral toxicity : LD50 Oral (Rat): 751 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 440 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit

Assessment : Corrosive

Method : OECD Test Guideline 404

Serious eye damage/eye irritation

Causes serious eye damage.

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version
3.0

Revision Date:
2022/02/25

SDS Number:
100000003307

Date of last issue: 2020/11/14
Date of first issue: 2018/05/24

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l
Exposure time: 72 h

4-methylimidazole:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 34 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 2 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version
3.0

Revision Date:
2022/02/25

SDS Number:
100000003307

Date of last issue: 2020/11/14
Date of first issue: 2018/05/24

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3267
Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(3,3'-oxybis(ethyleneoxy)bis(propylamine))
Class : 8
Packing group : III
Labels : 8

IATA-DGR

UN/ID No. : UN 3267
Proper shipping name : Corrosive liquid, basic, organic, n.o.s.
(3,3'-oxybis(ethyleneoxy)bis(propylamine))
Class : 8
Packing group : III
Labels : Corrosive
Packing instruction (cargo) : 856

SAFETY DATA SHEET

SikaPower®-4720 Part B



| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 3.0 | Revision Date: 2022/02/25 | SDS Number: 100000003307 | Date of last issue: 2020/11/14 Date of first issue: 2018/05/24 |
|----------------|------------------------------|-----------------------------|---|

aircraft)
Packing instruction (passenger aircraft) : 852

IMDG-Code

UN number : UN 3267
Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(3,3'-oxybis(ethyleneoxy)bis(propylamine))
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Hazardous Substance Act : Conditions of restriction for the following entries should be considered:
Not applicable

Emergency Decree on Controlling the Use of Volatile Substances : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 2% w/w

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

SAFETY DATA SHEET

SikaPower®-4720 Part B



| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 3.0 | Revision Date: 2022/02/25 | SDS Number: 100000003307 | Date of last issue: 2020/11/14 Date of first issue: 2018/05/24 |
|----------------|------------------------------|-----------------------------|---|

| | | |
|--------|---|--|
| CAS | : | Chemical Abstracts Service |
| DNEL | : | Derived no-effect level |
| EC50 | : | Half maximal effective concentration |
| GHS | : | Globally Harmonized System |
| IATA | : | International Air Transport Association |
| IMDG | : | International Maritime Code for Dangerous Goods |
| LD50 | : | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : | Occupational Exposure Limit |
| PBT | : | Persistent, bioaccumulative and toxic |
| PNEC | : | Predicted no effect concentration |
| REACH | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | : | Substances of Very High Concern |
| vPvB | : | Very persistent and very bioaccumulative |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

TH / EN