

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version 1.0

SDS Number: 100000003307

Revision Date: 2018/05/24

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaPower®-4720 Part B
Product code : 100000003307
Type of product : liquid

Recommended use of the chemical and restrictions on use

Product use : Adhesive

Manufacturer or supplier's details

Company : Sika (Thailand) Limited
700/37 Moo. 5 Amata Nakorn Estate
Bangna-Trad Km.57
Tambol Klong Tamhru
Muang District
Chonburi 20000
Thailand

Telephone : +66 3810 9500

Emergency telephone number : +66 3821 4270-85

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 1
Serious eye damage/eye irritation : Category 1
Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version 1.0

SDS Number: 100000003307

Revision Date: 2018/05/24

P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration (%) |
|--|------------|-------------------|
| 3,3'-oxybis(ethyleneoxy)bis(propylamine) | 4246-51-9 | >= 10 - < 20 |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | >= 5 - < 10 |
| 2-ethyl-4-methylimidazole | 931-36-2 | >= 1 - < 3 |
| 2-methylpentane-1,5-diamine | 15520-10-2 | >= 1 - < 3 |
| bis[(dimethylamino)methyl]phenol | 71074-89-0 | >= 1 - < 3 |

4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version 1.0

SDS Number: 100000003307

Revision Date: 2018/05/24

- wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.
corrosive effects
sensitising effects
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes severe burns.
- Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version 1.0

SDS Number: 100000003307

Revision Date: 2018/05/24

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version 1.0

SDS Number: 100000003307

Revision Date: 2018/05/24

- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous liquid
- Colour : beige
- Odour : amine-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 93.4 °C (> 200.1 °F)
Method: closed cup
- Evaporation rate : No data available
- Flammability : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : 0.0133322 hPa (0.010 mmHg)
- Relative vapour density : No data available
- Density : 1.13 g/cm³ (20 °C (68 °F) ())
- Solubility(ies)
Water solubility : insoluble
- Partition coefficient: n-octanol/water : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version 1.0

SDS Number: 100000003307

Revision Date: 2018/05/24

| | |
|----------------------|--------------------------------------|
| Viscosity | |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : > 10000 mm ² /s (40 °C) |
| Explosive properties | : No data available |
| Molecular weight | : No data available |

10. STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : The product is chemically stable. |
| Possibility of hazardous reactions | : Stable under recommended storage conditions. |
| Conditions to avoid | : No data available |
| Incompatible materials | : No data available |
| No decomposition if stored and applied as directed. | |

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

3,3'-oxybis(ethyleneoxy)bis(propylamine):

| | |
|-----------------------|---------------------------------------|
| Acute oral toxicity | : LD50 Oral (Rat): ca. 3,560 mg/kg |
| Acute dermal toxicity | : LD50 Dermal (Rabbit): > 2,500 mg/kg |

2-methylpentane-1,5-diamine:

| | |
|-----------------------|-------------------------------------|
| Acute oral toxicity | : LD50 Oral (Rat): 1,170 mg/kg |
| Acute dermal toxicity | : LD50 Dermal (Rabbit): 1,870 mg/kg |

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version 1.0

SDS Number: 100000003307

Revision Date: 2018/05/24

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10
- 100 mg/l
Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

SAFETY DATA SHEET

SikaPower®-4720 Part B



Version 1.0

SDS Number: 100000003307

Revision Date: 2018/05/24

UN number : UN 3267
Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O. S.
(3,3'-oxybis(ethyleneoxy)bis(propylamine))
Class : 8
Packing group : III
Labels : 8

IATA-DGR

UN/ID No. : UN 3267
Proper shipping name : Corrosive liquid, basic, organic, n.o.s.
(3,3'-oxybis(ethyleneoxy)bis(propylamine))
Class : 8
Packing group : III
Labels : 8
Packing instruction (cargo aircraft) : 856
Packing instruction (passenger aircraft) : 852

IMDG-Code

UN number : UN 3267
Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(3,3'-oxybis(ethyleneoxy)bis(propylamine))
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

Hazardous Substance Act B.E. 2535 : Not applicable

Emergency Decree on Controlling the Use of Volatile Substances B.E. 2533 : Not applicable

VOC-EU (solvent) : 22.6 g/l

16. OTHER INFORMATION

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.