



BUILDING TRUST



PRODUCT DATA SHEET

LANKO LOFT WAX

WATER BASED LOFT WAX

DESCRIPTION

LANKO LOFT WAX is water based and non solvent wax

USES

LANKO LOFT WAX can be used as a decorative interior and exterior wall with a shiny finish and stain protection

CHARACTERISTICS / ADVANTAGES

- Non-solvent and non-flammable wax
- Non-toxic and odorless
- Water repellent
- Prevent stains
- Shiny finish

PRODUCT INFORMATION

Composition	Synthetic resins, mineral filler and admixtures
Packaging	5 kg. pail
Appearance / Colour	White creamy
Shelf life	12 months from date of production if stored in undamaged and unopened, original sealed packaging
Storage conditions	Store in dry condition and protected from direct sunshine
pH-Value	8 - 10

APPLICATION INFORMATION

Consumption	Approx. 50 - 70 m ² / 5 kg. pail
Ambient air temperature	+5°C to +35°C

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

1. Apply Lanko Loft to meet the the required thickness and texture and allow a sufficient drying time between the coats for 30-45 minutes.
2. Can use sand paper no. 380 to smooth the surface

MIXING

Ready-to-use paste. No water must be added.

APPLICATION

Apply LANKO LOFT WAX on the surface by using plastic paddle after LANKO LOFT powder has been applied.

The surface must be clean, dry (2-4 hours after applying LANKO LOFT powder, depends on weather condition) and dust free. Two coats of wax will be more water repellent and have a more shiny finish. (wait 30 minutes between coat.)

IMPORTANT CONSIDERATIONS

- Temperature range for use : 5°C to 35°C
- Do not apply on hot substrate, decrease the temperature of substrate by damp cloth or sponge.
- Not suitable for structural crack subject to movement.
- Protect for 24 hours in case of heavy rain or very sunny.
- Avoid dust before wax application.
- Do not use on floor.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Thailand) Limited
700/37 Moo 5 Amata City Chonburi
Industrial Estate, T. Klong Tamhru
A. Muang, Chonburi 20000, Thailand
Tel : +66 3810 9500
E-mail : sikathai@th.sika.com
Website: tha.sika.com



PRODUCT DATA SHEET
LANKO LOFT WAX
September 2020, Version 01.01
02189010000000059

LANKOLOFTWAX-en-THLANKO-(09-2020)-1-1.pdf