

SAFETY DATA SHEET

Sikafloor®-264 HC N Part A



Version 2.0

SDS Number: 000000601221

Revision Date: 2020/04/29

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-264 HC N Part A
Product code : 000000601221
Type of product : liquid

Manufacturer or supplier's details

Company : Sika (Thailand) Limited
700/37 Moo. 5 Amata Nakorn Estate
Bangna-Trad Km.57
Tambol Klong Tamhru
Muang District
Chonburi 20000
Thailand
Telephone : +66 3810 9500
Emergency telephone number : +66 3821 4270-85
Telefax : +66 3821 4286
E-mail address : Sikathai@th.sika.com

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2A
Skin sensitisation : Category 1
Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)
Short-term (acute) aquatic hazard : Category 2
Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

Sikafloor®-264 HC N Part A



Version 2.0

SDS Number: 000000601221

Revision Date: 2020/04/29

Precautionary statements : **Prevention:**
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P391 Collect spillage.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 30 - < 50
Quartz (SiO ₂) <5μm	14808-60-7	>= 10 - < 20
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 1 - < 10
benzyl alcohol	100-51-6	>= 1 - < 10

4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

SAFETY DATA SHEET

Sikafloor®-264 HC N Part A



Version 2.0

SDS Number: 000000601221

Revision Date: 2020/04/29

Most important symptoms and effects, both acute and delayed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention. irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Causes damage to organs through prolonged or repeated exposure if inhaled.
Notes to physician	: Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific hazards during fire-fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Normal measures for preventive fire protection.
Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).



Do not get in eyes, on skin, or on clothing.
 For personal protection see section 8.
 Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Smoking, eating and drinking should be prohibited in the application area.
 Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂) <5µm	14808-60-7	TWA (Respirable dust)	0.025 mg/m ³	TH OEL
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should

SAFETY DATA SHEET

Sikafloor®-264 HC N Part A



Version 2.0

SDS Number: 000000601221

Revision Date: 2020/04/29

Skin and body protection	: be used when a risk assessment indicates this is necessary. : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: grey
Odour	: very faint
Odour Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 93.3 °C (> 199.9 °F) Method: closed cup
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 0.01 hPa (0.01 mmHg)
Relative vapour density	: No data available
Density	: 1.6 g/cm ³ (20 °C (68 °F) ())
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 7 mm ² /s (40 °C)
Explosive properties	: No data available

SAFETY DATA SHEET

Sikafloor®-264 HC N Part A



Version 2.0

SDS Number: 000000601221

Revision Date: 2020/04/29

Molecular weight : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.
Chemical stability : The product is chemically stable.
Possibility of hazardous reactions : Stable under recommended storage conditions.
Conditions to avoid : No data available
Incompatible materials : No data available
No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

**Aspiration toxicity**

Not classified based on available information.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):**Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates : Exposure time: 48 h**benzyl alcohol:**Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 hToxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates : Exposure time: 48 h**Persistence and degradability**

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**Additional ecological infor- : An environmental hazard cannot be excluded in the event of
mation : unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.**13. DISPOSAL CONSIDERATIONS****Disposal methods**Waste from residues : The product should not be allowed to enter drains, water
courses or the soil.
Do not contaminate ponds, waterways or ditches with chemi-
cal or used container.
Send to a licensed waste management company.
Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SAFETY DATA SHEET

Sikafloor®-264 HC N Part A



Version 2.0

SDS Number: 000000601221

Revision Date: 2020/04/29

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(epoxy resin)
Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(epoxy resin)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(epoxy resin)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

Hazardous Substance Act B.E. 2535 : Conditions of restriction for the following entries should be considered:
Not applicable

SAFETY DATA SHEET

Sikafloor®-264 HC N Part A



Version 2.0

SDS Number: 000000601221

Revision Date: 2020/04/29

Emergency Decree on Controlling the Use of Volatile Substances B.E. 2533 : Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 2.44 %
VOC content excluding water

:

16. OTHER INFORMATION

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.