

## PRODUCT DATA SHEET

# Sarnafast® SBF-6.0 x L

Carbon Steel Fastener for Mechanical Fastening Roof Waterproofing Membranes and Thermal Insulation into Roof Structures

### DESCRIPTION

Case hardened carbon steel fastener with a drilling tip for mechanical fastening roof waterproofing membranes and thermal insulation into roof structures.

### USES

Steel fastener for mechanical fastening roof waterproofing membranes and thermal insulation into steel, concrete or timber decks. Used in combination with:

- Sarnafast® Tube SFT-50
- Sarnabar® Tube SBT-20
- Sarnafast® KTL
- Sarnafast® DTL
- SikaRoof® Induction Welding Disc FPO/PVC
- Sarnabar® Fastening Profiles

### FEATURES

- Fast and easy installation due to optimised drill tip
- High pull-out values in thin steel substrates due to 6 mm wide, asymmetric thread
- High quality corrosion protection, environment friendly, free of Chromium VI



### CERTIFICATES AND TEST REPORTS

- European Technical Approval ETA-08/0262
- Factory Mutual Class No. 4470

## PRODUCT INFORMATION

Packaging	Refer to current price list for packaging variations.
Shelf life	5 years from date of production.
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions. Always refer to packaging.

## TECHNICAL INFORMATION

### APPLICATION INFORMATION

Ambient air temperature	-20 °C min. / +60 °C max.
Substrate temperature	-25 °C min. / +60 °C max.

### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### IMPORTANT CONSIDERATIONS

- Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.
- The use of the Sarnafast Fastener SBF-6.0 x L is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

### ECOLOGY, HEALTH AND SAFETY

#### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

### APPLICATION INSTRUCTIONS

#### APPLICATION METHOD / TOOLS

Refer to the relevant section in the Sika application manual and installation instructions:

a) on steel deck:

Substrate material quality:	S235 – S320GD
Substrate material thickness:	min. 0.5 mm
	max. 2 × 1.25 mm or 1 × 2.0 mm
Setting depth:	min. 20 mm
b) on concrete deck:	
Substrate material quality:	min. C12/C15
Setting depth:	min. 32 mm
Drilling diameter	5.0 mm (drilling depth min. 40 mm)
b) on timber deck:	
Substrate material thickness:	min. 18 mm
Setting depth:	min. 30 mm

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika (Thailand) Limited

700/37 Moo 5 Amata City Chonburi  
Industrial Estate, T. Klong Tamhru  
A. Muang, Chonburi 20000, Thailand  
Tel : +66 3810 9500  
E-mail : sikathai@th.sika.com  
Website: tha.sika.com



### Product Data Sheet

Sarnafast® SBF-6.0 x L  
November 2024, Version 01.01  
020945051100001018

SarnafastSBF-60xL-en-TH-(11-2024)-1-1.pdf