

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-264 HC Part B
Product code : 000000121422
Type of product : liquid

Recommended use of the chemical and restrictions on use

Product use : Epoxy coating, Product is not intended for consumer use

Manufacturer or supplier's details

Company : Sika (Thailand) Limited
700/37 Moo. 5 Amata Nakorn Estate
Bangna-Trad Km.57
Tambol Klong Tamhru
Muang District
Chonburi 20000
Thailand

Telephone : +66 3810 9500

Emergency telephone number : +66 3821 4270-85

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4
Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 5
Skin corrosion/irritation : Category 1
Serious eye damage/eye irritation : Category 1
Skin sensitisation : Category 1
Reproductive toxicity : Category 2
Acute aquatic toxicity : Category 2
Chronic aquatic toxicity : Category 1

GHS Label element

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H227 Combustible liquid.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H333 May be harmful if inhaled.
H361 Suspected of damaging fertility or the unborn child.
H401 Toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P281 Use personal protective equipment as required.
Response:
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P391 Collect spillage.
Storage:
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Polyaminoamide

Hazardous components

| Chemical Name | CAS-No. | Concentration (%) |
|--|-------------|-------------------|
| benzyl alcohol | 100-51-6 | >= 30 - < 50 |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine | 2855-13-2 | >= 10 - < 20 |
| m-phenylenebis(methylamine) | 1477-55-0 | >= 10 - < 20 |
| Hydrocarbons, C9, aromatics | 64742-95-6 | >= 1 - < 10 |
| Phenol, dodecyl-, branched | 121158-58-5 | >= 1 - < 10 |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2 | >= 1 - < 10 |

4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.
corrosive effects
sensitising effects

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

Gastrointestinal discomfort
Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Harmful if swallowed.
May cause an allergic skin reaction.
Causes serious eye damage.
May be harmful if inhaled.
Suspected of damaging fertility or the unborn child.
Causes severe burns.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)
- Unsuitable extinguishing media : Water
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-----------------------------|------------|-------------------------------|--|-------|
| m-phenylenebis(methylamine) | 1477-55-0 | C | 0.1 mg/m ³ | ACGIH |
| Hydrocarbons, C9, aromatics | 64742-95-6 | TWA | 200 mg/m ³ (total hydrocarbon vapor) | ACGIH |

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : yellow

Odour : amine-like

Odour Threshold : No data available

pH : ca. 11

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : ca. 68 °C (154 °F)
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 4.9996 hPa (3.750 mmHg)

Relative vapour density : No data available

Density : ca. 1 g/cm³ (20 °C (68 °F) ())

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : ca.
420 °C (788 °F)

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

| | |
|--|-------------------------------------|
| Viscosity, kinematic | : > 20.5 mm ² /s (40 °C) |
| Molecular weight | : No data available |
| Volatile organic compounds (VOC) content | : No data available |

10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : The product is chemically stable. |
| Possibility of hazardous reactions | : Stable under recommended storage conditions. |
| Conditions to avoid | : No data available |
| Incompatible materials | : No data available |

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.
May be harmful if inhaled.

Components:

benzyl alcohol:

| | |
|---------------------------|--|
| Acute oral toxicity | : LD50 Oral (Rat): 1,620 mg/kg |
| Acute inhalation toxicity | : LC50 (Rat): > 4.178 mg/l Exposure time: 4 h Test atmosphere: dust/mist |

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

| | |
|-----------------------|---------------------------------------|
| Acute oral toxicity | : LD50 Oral (Rat): 1,030 mg/kg |
| Acute dermal toxicity | : LD50 Dermal (Rabbit): > 2,000 mg/kg |

m-phenylenebis(methylamine):

| | |
|---------------------------|---|
| Acute oral toxicity | : LD50 Oral (Rat): 930 mg/kg |
| Acute inhalation toxicity | : LC50 (Rat): 1.34 mg/l Exposure time: 4 h Test atmosphere: dust/mist |
| Acute dermal toxicity | : LD50 Dermal (Rat): > 3,100 mg/kg |

Hydrocarbons, C9, aromatics:

| | |
|-----------------------|---------------------------------------|
| Acute oral toxicity | : LD50 Oral (Rat): > 2,000 mg/kg |
| Acute dermal toxicity | : LD50 Dermal (Rabbit): > 2,000 mg/kg |

Phenol, dodecyl-, branched:

| | |
|---------------------|--------------------------------|
| Acute oral toxicity | : LD50 Oral (Rat): 2,140 mg/kg |
|---------------------|--------------------------------|

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9 mg/l
Exposure time: 72 h

Phenol, dodecyl-, branched:

Toxicity to fish : LC50 (Fish): 0.14 mg/l
Exposure time: 96 h
Method: see user defined free text

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.01 - 0.1 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 10

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulation

UNRTDG

UN number : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, solvent naphtha)
Class : 8
Packing group : III
Labels : 8

IATA-DGR

UN/ID No. : UN 1760
Proper shipping name : Corrosive liquid, n.o.s.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, solvent naphtha)
Class : 8
Packing group : III
Labels : 8
Packing instruction (cargo aircraft) : 856
Packing instruction (passen- : 852

SAFETY DATA SHEET

Sikafloor®-264 HC Part B



Version 1.0

MSDS Number: 000000121422

Revision Date: 2015/08/06

ger aircraft)

IMDG-Code

UN number : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, solvent
naphtha)
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable
Hazardous Substance Act B.E. 2535 : Not applicable
Emergency Decree on Controlling the Use of Volatile Substances B.E. 2533 : Not applicable
Notification of Ministry of Interior on Working Safety Relating to Hazardous Chemicals B.E. 2534 : benzyl alcohol
3-aminomethyl-3,5,5-trimethylcyclohexylamine
2,4,6-tris(dimethylaminomethyl)phenol

16. OTHER INFORMATION

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.