

PRODUCT DATA SHEET

SikaWall® Skim Coat TH

POWDER FOR SURFACE FINISHING

DESCRIPTION

SikaWall® Skim Coat TH is a mixture of powder to be mixed with water for repairing surface defects in concrete or render. A smooth surface is obtained by eliminating blemishes such as grooves, seams, fine cracks and rock pockets.

USES

SikaWall® Skim Coat TH is a surface finishing coating for reinforced concrete surfaces, precast concrete panels, brick and block works.

CHARACTERISTICS / ADVANTAGES

SikaWall® Skim Coat TH can be applied to both interior and exterior substrates.

SikaWall® Skim Coat TH has the following advantages:

- Durable hard wearing surface
- Easy to use
- Excellent bonding to cementitious substrates
- Quick application time

PRODUCT INFORMATION

| | |
|----------------------------|--|
| Packaging | 20 kg/bag |
| Appearance / Colour | Powder Grey, White |
| Shelf life | 9 months from date of production if stored in undamaged and unopened, original sealed packaging. |
| Storage conditions | Store in dry condition and protected from direct sunshine. |
| Density | 1.4 kg/L (Bulk) |
| Maximum Grain Size | 0.1 mm |

APPLICATION INFORMATION

| | |
|--------------------|--|
| Consumption | Approx. 1.9 kg/m ² per 1 mm thickness |
| Pot Life | Approximately 45 minutes (at 30°C) |

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

The substrates must be clean, sound and free from loose particles. Dust and oil must be removed before application.

MIXING

Mix SikaWall® Skim Coat TH with water until a homogenous mixture is achieved. Leave the mixture to stand for several minutes.

- **For grey color:** use water 7.0-7.4 litres (35%-37%) per 1 bag of SikaWall® Skim Coat TH (20 kg)
- **For white color:** use water 7.4-7.8 litres (37%-39%) per 1 bag of SikaWall® Skim Coat TH (20 kg)

APPLICATION

Apply the mixture to the prepared substrate with trowel or putty knife. One or more coats may be applied depending on the desired finish. The application thickness is approx. 0.5 - 2.0 mm. The surface of SikaWall® Skim Coat TH can be sanded.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Thailand) Limited

700/37 Moo 5 Amata Nakorn Estate
KM.57 Bangna Trad Rd., T. Klong Tamhru
A. Muang, Chonburi 20000, Thailand
Tel : +66 3810 9500
E-mail : sikathai@th.sika.com
www.sika.co.th



Product Data Sheet
SikaWall® Skim Coat TH
January 2019, Version 01.01
020406010030000080

SikaWallSkimCoatTH-en-TH-(01-2019)-1-1.pdf