



LANKO

BUILDING TRUST



PRODUCT DATA SHEET

LANKO 107 WALL PUTTY

READY TO USE ACRYLIC PUTTY

DESCRIPTION

LANKO 107 WALL PUTTY is a ready to use acrylic wall putty for filling or patching cracks, nail holes, grooves, seams air bubbles and rock pocket. Its ready to use formula spreads easily for fast repairs that will not crack, crumble or flake.

USES

- LANKO 107 WALL PUTTY is suitable for wall and ceiling, interior and exterior application
- LANKO 107 WALL PUTTY can be used on substrates including concrete, brick, lightweight block and wood

CHARACTERISTICS / ADVANTAGES

- Ready to use, no mixing required
- Fast drying
- No shrinkage
- Good adhesion
- Anti-black mold
- Can be sanded and over painted

PRODUCT INFORMATION

Composition	Synthetic resins, mineral filler and admixtures
Packaging	1.5 kg/pail, 5 kg/pail
Appearance / Colour	White paste
Shelf life	12 months from date of production if stored in undamaged and unopened, original sealed packaging
Storage conditions	Store in dry condition and protected from direct sunshine
Density	1.7 - 1.8 kg/L
pH-Value	8 - 10

TECHNICAL INFORMATION

Tensile adhesion strength	≥ 0.5 MPa at 28 days (at 1 mm thickness)
---------------------------	--

APPLICATION INFORMATION

Layer thickness	0.3 - 4 mm
Ambient air temperature	+10°C to +35°C

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

The surface must be clean, dry and free of dust, oil, paint and other contamination. Remove all excess seams or edge mechanically to level the surface.

MIXING

LANKO 107 WALL PUTTY is supplied ready to use - no water or other mixing is added.

APPLICATION

Lanko 107 Wall Putty can be applied with putty knife in layer thicknesses from 0.3 - 4 mm. When filling deeper holes or cracks above 4 mm the filler must be applied in several layers and must be allowed to almost dry before each subsequent layer is applied. Allow a sufficient drying time for 10-30 minutes, use sand paper to remove the remaining from the surface. Allow 24 hours curing time before applying covering material.

IMPORTANT CONSIDERATIONS

- Do not apply to damp substrate.
- Do not add any water or other product.
- Not suitable for movement joint.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Thailand) Limited

700/37 Moo 5 Amata City Chonburi
Industrial Estate, T. Klong Tamhru
A. Muang, Chonburi 20000, Thailand
Tel : +66 3810 9500
E-mail : sikathai@th.sika.com
Website: tha.sika.com



PRODUCT DATA SHEET
LANKO 107 WALL PUTTY
July 2020, Version 02.01
021825201000000005

LANKO107WALLPUTTY-en-THLANKO-(07-2020)-2-1.pdf