

SAFETY DATA SHEET

Sikafloor® ColorSeal



Version 1.0

MSDS Number: 000000611732

Revision Date: 2015/09/25

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor® ColorSeal

Product code : 000000611732

Type of product : liquid

Recommended use of the chemical and restrictions on use

Product use : Flooring system

Manufacturer or supplier's details

Company : Sika (Thailand) Limited
700/37 Moo. 5 Amata Nakorn Estate
Bangna-Trad Km.57
Tambol Klong Tamhru
Muang District
Chonburi 20000
Thailand

Telephone : +66 3810 9500

Emergency telephone number : +66 3821 4270-85

Telefax : +66 3821 4286

E-mail address : Sikathai@th.sika.com

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 5

Acute toxicity (Dermal) : Category 5

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (hearing organs)

Aspiration hazard : Category 1

GHS Label element

SAFETY DATA SHEET

Sikafloor® ColorSeal



Version 1.0

MSDS Number: 000000611732

Revision Date: 2015/09/25

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H313 + H333 May be harmful in contact with skin or if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H373 May cause damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.
Precautionary statements	:	Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER or doctor/ physician if you feel unwell. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Disposal:

SAFETY DATA SHEET

Sikafloor® ColorSeal



Version 1.0

MSDS Number: 000000611732

Revision Date: 2015/09/25

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
xylene	1330-20-7	>= 30 - < 50
ethylbenzene	100-41-4	>= 10 - < 20

4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Risk of serious damage to the lungs (by aspiration).
irritant effects
Aspiration may cause pulmonary oedema and pneumonitis.
Cough
Respiratory disorder
Excessive lachrymation
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
May be fatal if swallowed and enters airways.
May be harmful in contact with skin or if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated

SAFETY DATA SHEET

Sikafloor® ColorSeal



Version 1.0

MSDS Number: 000000611732

Revision Date: 2015/09/25

exposure if inhaled.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.



Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	TH OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

Sikafloor® ColorSeal



Version 1.0

MSDS Number: 000000611732

Revision Date: 2015/09/25

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous
Colour	: various
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: 35 °C (95 °F) Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 1 %(V)
Vapour pressure	: 7.9993 hPa (6.000 mmHg)
Relative vapour density	: No data available
Density	: ca. 1.1 g/cm ³ (20 °C (68 °F) ())
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 400 - 500 mPa.s (20 °C)
Viscosity, kinematic	: No data available
Molecular weight	: No data available
Volatile organic compounds (VOC) content	: No data available

SAFETY DATA SHEET

Sikafloor® ColorSeal



Version 1.0

MSDS Number: 000000611732

Revision Date: 2015/09/25

10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: No data available
Hazardous decomposition products	: No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

No data available

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (hearing organs) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

SAFETY DATA SHEET

Sikafloor® ColorSeal



Version 1.0

MSDS Number: 000000611732

Revision Date: 2015/09/25

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulation

UNRTDG

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III
Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E

SAFETY DATA SHEET

Sikafloor® ColorSeal



Version 1.0

MSDS Number: 000000611732

Revision Date: 2015/09/25

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Notification of Ministry of Interior on Working Safety : xylene
Relating to Hazardous Chemicals B.E. 2534 ethylbenzene

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

Hazardous Substance Act B.E. 2535 : Not applicable

Emergency Decree on Controlling the Use of Volatile : xylene
Substances B.E. 2533

16. OTHER INFORMATION

Date format : yyyy/mm/dd

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.